

Safety data sheet

Page: 1/10

BASF Safety data sheet

Date / Revised: 12.09.2018

Product: **MasterFlow 618 PART A**

Version: 4.0

(30647163/SDS_GEN_AU/EN)

Date of print 17.09.2018

1. Substance/preparation and manufacturer/supplier identification

MasterFlow 618 PART A

Use: Product for construction chemicals

Manufacturer/supplier:

BASF Australia Limited (ABN 62 008 437 867)

Level 12, 28 Freshwater Place Southbank

Victoria 3006, AUSTRALIA

Telephone: +61 3 8855-6600

Telefax number: +61 3 8855-6511

Emergency information:

BASF Emergency Advice Number: 1800 803 440 (24h) [within Australia]

BASF Emergency Advice Number: + 61 3 8855 6666 [outside Australia]

2. Hazard identification

Classification of the substance and mixture:

Skin corrosion/irritation: Cat. 2

Serious eye damage/eye irritation: Cat. 2A

Skin sensitization: Cat. 1

Hazardous to the aquatic environment - acute: Cat. 2

Hazardous to the aquatic environment - chronic: Cat. 2

Label elements and precautionary statement:

Pictogram:



Signal Word:
Warning

Hazard Statement:

H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H401	Toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P273	Avoid release to the environment.
P260	Do not breathe dust/gas/mist/vapours.
P272	Contaminated work clothing should not be allowed out of the workplace.
P264	Wash with plenty of water and soap thoroughly after handling.
P280	Wear protective gloves and eye/face protection.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P311	Call a POISON CENTER or doctor/physician.
P303 + P352	IF ON SKIN (or hair): Wash with plenty of soap and water.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P391	Collect spillage.

Precautionary Statements (Disposal):

P501	Dispose of contents/container to hazardous or special waste collection point.
------	---

Other hazards which do not result in classification:

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

3. Composition/information on ingredients

Chemical nature

Blend based on: epoxy resin

Hazardous ingredients

Reaction product: bisphenol-A-(epichlorhydrin)-Epoxy resin (number average molecular weight <= 700)

Content (W/W): >= 25 % - < 50 %	Skin Corr./Irrit.: Cat. 2
CAS Number: 25068-38-6	Eye Dam./Irrit.: Cat. 2A
	Skin Sens.: Cat. 1A
	Aquatic Acute: Cat. 2
	Aquatic Chronic: Cat. 2

Neodecanoic acid, oxiranylmethyl ester

BASF Safety data sheet
Date / Revised: 12.09.2018
Product: **MasterFlow 618 PART A**

Version: 4.0

(30647163/SDS_GEN_AU/EN)

Date of print 17.09.2018

Content (W/W): $\geq 5\%$ - $< 10\%$
CAS Number: 26761-45-5

Skin Sens.: Cat. 1
Muta.: Cat. 2
Aquatic Chronic: Cat. 2

4. First-Aid Measures

General advice:

First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

On skin contact:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Rinse mouth immediately and then drink plenty of water, seek medical attention. Do not induce vomiting.

Note to physician:

Symptoms: Eye irritation, skin irritation, allergic contact dermatitis

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Suitable extinguishing media:

foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:

water jet

Specific hazards:

carbon dioxide, carbon monoxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

Special protective equipment:

Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental Release Measures

Personal precautions:

Do not breathe vapour/aerosol/spray mists. Wear eye/face protection. If exposed to high vapour concentration, leave area immediately. Use personal protective clothing. Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions:

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods for cleaning up or taking up:

For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.

For large amounts: Pump off product.

7. Handling and Storage

Handling

Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. No special measures necessary provided product is used correctly.

Storage

Observe VCI storage rules.

Suitable materials for containers: tinned carbon steel (Tinplate), Carbon steel (Iron), Polypropylene (PP)

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight.

8. Exposure controls and personal protection

Components with occupational exposure limits

Limestone, 1317-65-3;

TWA value 10 mg/m³ (OEL (AU)), Inhalable dust

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Combination filter for gases/vapours of organic, inorganic, acid inorganic and alkaline compounds (e.g. EN 14387 Type ABEK).

Hand protection:

Chemical resistant protective gloves (EN 374)

Manufacturer's directions for use should be observed because of great diversity of types.

(30647163/SDS_GEN_AU/EN)

Date of print 17.09.2018

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN 374):
butyl rubber (butyl) - 0.7 mm coating thickness
fluoroelastomer (FKM) - 0.7 mm coating thickness

Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN 374)
polyvinylchloride (PVC) - 0.7 mm coating thickness
chloroprene rubber (CR) - 0.5 mm coating thickness
nitrile rubber (NBR) - 0.4 mm coating thickness

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures:

Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

9. Physical and Chemical Properties

Form: highly viscous
Colour: white
Odour: characteristic
Odour threshold: No applicable information available.

pH value:
not available

Melting temperature: not determined
Boiling range: > 100 °C

Flash point:
not applicable

Flammability (solid/gas): not flammable

Lower explosion limit: As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with the intended use.

Upper explosion limit: As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with the intended use.

Ignition temperature: Study does not need to be conducted.

Thermal decomposition: No decomposition if stored and handled as prescribed/indicated.

Self ignition: not self-igniting

Self heating ability: It is not a substance capable of spontaneous heating.

Explosion hazard: not explosive

Fire promoting properties: not fire-propagating

Vapour pressure: The product has not been tested.

Density: 1.10 - 1.16 g/cm³
(25 °C)

Bulk density: not applicable

Solubility in water: insoluble

Miscibility with water: immiscible

Hygroscopy: Non-hygroscopic

Solubility (qualitative) solvent(s): organic solvents
insoluble

Partitioning coefficient n-octanol/water (log Pow):
not applicable for mixtures

Viscosity, dynamic: No data available.

Viscosity, kinematic: not applicable

Solids content: 85 - 95 %

Other Information:

If necessary, information on other physical and chemical parameters is indicated in this section.

10. Stability and Reactivity

Conditions to avoid:
See MSDS section 7 - Handling and storage.

Thermal decomposition: No decomposition if stored and handled as prescribed/indicated.

Substances to avoid:
strong acids, strong bases, strong oxidizing agents, strong reducing agents

Corrosion to metals: No corrosive effect on metal.

Hazardous reactions:
The product is stable if stored and handled as prescribed/indicated.

No hazardous decomposition products if stored and handled as prescribed/indicated.

11. Toxicological Information

Acute toxicity

Assessment of acute toxicity:
Virtually nontoxic after a single ingestion. Based on available Data, the classification criteria are not met.

Irritation

Assessment of irritating effects:
Eye contact causes irritation. Skin contact causes irritation.

Respiratory/Skin sensitization

Assessment of sensitization:
Sensitization after skin contact possible.

Germ cell mutagenicity

Assessment of mutagenicity:
The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity:
Based on the ingredients there is no suspicion of a carcinogenic effect in humans. Based on available Data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity:

The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Developmental toxicity

Assessment of teratogenicity:

The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Specific target organ toxicity (single exposure):

| Remarks: Based on available Data, the classification criteria are not met.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

No reliable data was available concerning repeated dose toxicity. Based on available Data, the classification criteria are not met.

Aspiration hazard

| No aspiration hazard expected.

Other relevant toxicity information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

12. Ecological Information

Ecotoxicity

Assessment of aquatic toxicity:

Acutely toxic for aquatic organisms. May cause long-term adverse effects in the aquatic environment. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Mobility

Assessment transport between environmental compartments:

The substance will not evaporate into the atmosphere from the water surface.

Following exposure to soil, adsorption to solid soil particles is probable, therefore contamination of groundwater is not expected.

Persistence and degradability

Assessment biodegradation and elimination (H₂O):

The product is virtually insoluble in water and can thus be separated from water mechanically in suitable effluent treatment plants.

Bioaccumulation potential

Bioaccumulation potential:

Because of the product's consistency and low water solubility, bioavailability is improbable.

Additional information

Other ecotoxicological advice:

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

13. Disposal Considerations

Observe national and local legal requirements.

Residues should be disposed of in the same manner as the substance/product.

Contaminated packaging:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

14. Transport Information

Domestic transport:

Packing group:	III
ID number:	UN 3082
Transport hazard class(es):	9, EHSM
Proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains BISPHENOL-A-EPICHLORHYDRIN RESINS M <=700)

Further information

Hazchem Code:3Z

IERG Number:47

Sea transport

IMDG

Packing group:	III
ID number:	UN 3082
Transport hazard class(es):	9, EHSM
Marine pollutant:	YES
Proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains BISPHENOL-A-EPICHLORHYDRIN RESINS M <=700)

Air transport

IATA/ICAO

BASF Safety data sheet
Date / Revised: 12.09.2018
Product: **MasterFlow 618 PART A**

Version: 4.0

(30647163/SDS_GEN_AU/EN)

Date of print 17.09.2018

Packing group:	III
ID number:	UN 3082
Transport hazard class(es):	9, EHSM
Proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains BISPHENOL-A-EPICHLORHYDRIN RESINS M <=700)

Further information

Environmentally Hazardous Substances meeting the description of UN 3077 or UN 3082 are not subjected to the Australian Dangerous Goods Code when transported by road or rail in packagings not exceeding 500 kg(L) or IBCs.

15. Regulatory Information

Other regulations

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP): Schedule 5

Registration status:

AICS, AU released / listed

16. Other Information

Vertical lines in the left hand margin indicate an amendment from the previous version.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.