

Safety data sheet

Page: 1/10

BASF Safety data sheet

Date / Revised: 13.09.2017

Product: **MasterProtect 1812 PART B**

Version: 2.0

(30667421/SDS_GEN_AU/EN)

Date of print 13.09.2017

1. Substance/preparation and manufacturer/supplier identification

MasterProtect 1812 PART B

Use: Product for construction chemicals

Manufacturer/supplier:

BASF Australia Limited (ABN 62 008 437 867)

Level 12, 28 Freshwater Place Southbank

Victoria 3006, AUSTRALIA

Telephone: +61 3 8855-6600

Telefax number: +61 3 8855-6511

Emergency information:

BASF Emergency Advice Number: 1800 803 440 (24h) [within Australia]

BASF Emergency Advice Number: + 61 3 8855 6666 [outside Australia]

2. Hazard identification

Classification of the substance and mixture:

Acute toxicity: Cat. 4 (oral)

Acute toxicity: Cat. 4 (Inhalation - mist)

Acute toxicity: Cat. 5 (dermal)

Skin corrosion/irritation: Cat. 1B

Serious eye damage/eye irritation: Cat. 1

Skin sensitization: Cat. 1

Hazardous to the aquatic environment - acute: Cat. 1

Hazardous to the aquatic environment - chronic: Cat. 1

Label elements and precautionary statement:

Pictogram:



Signal Word:

| Danger

Hazard Statement:

H313	May be harmful in contact with skin.
H317	May cause an allergic skin reaction.
H314	Causes severe skin burns and eye damage.
H302 + H332	Harmful if swallowed or if inhaled
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P260	Do not breathe dust/mist/vapours.
P272	Contaminated work clothing should not be allowed out of the workplace.
P270	Do not eat, drink or smoke when using this product.
P264	Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

P310	Immediately call a POISON CENTER or doctor/physician.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P301 + P330 + P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P391	Collect spillage.
P362 + P364	Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Storage):

P405	Store locked up.
------	------------------

Precautionary Statements (Disposal):

P501	Dispose of contents/container to hazardous or special waste collection point.
------	---

Other hazards which do not result in classification:

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

3. Composition/information on ingredients

Chemical nature

Preparation based on: amines, fillers

Hazardous ingredients

| Benzyl alcohol

Content (W/W): $\geq 10\%$ - $< 50\%$	Flam. Liq.: Cat. 4
CAS Number: 100-51-6	Acute Tox.: Cat. 4 (oral)
	Acute Tox.: Cat. 4 (Inhalation - mist)
	Acute Tox.: Cat. 4 (dermal)
	Eye Dam./Irrit.: Cat. 2A
	Aquatic Acute: Cat. 3

| 1,3-Benzenedimethanamine

Content (W/W): $\geq 5\%$ - $< 15\%$	Acute Tox.: Cat. 4 (oral)
CAS Number: 1477-55-0	Acute Tox.: Cat. 4 (Inhalation - mist)
	Acute Tox.: Cat. 5 (dermal)
	Skin Corr./Irrit.: Cat. 1B
	Eye Dam./Irrit.: Cat. 1
	Skin Sens.: Cat. 1B
	Aquatic Acute: Cat. 3

| Formaldehyde, polymer with 1,3-benzenedimethanamine and phenol

Content (W/W): $\geq 10\%$ - $\leq 50\%$	Aquatic Acute: Cat. 1
CAS Number: 57214-10-5	Aquatic Chronic: Cat. 1

4. First-Aid Measures

General advice:

First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

On skin contact:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Rinse mouth immediately and then drink plenty of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.

Note to physician:

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

BASF Safety data sheet
Date / Revised: 13.09.2017
Product: **MasterProtect 1812 PART B**

Version: 2.0

(30667421/SDS_GEN_AU/EN)

Date of print 13.09.2017

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Suitable extinguishing media:
foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:
water jet

Specific hazards:
carbon dioxide, carbon monoxide, nitrogen oxides, fumes/smoke, carbon black, corrosive gases/vapours

Special protective equipment:
Wear a self-contained breathing apparatus.

Further information:
The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental Release Measures

Personal precautions:
Use personal protective clothing. Do not breathe vapour/aerosol/spray mists. Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions:
Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods for cleaning up or taking up:
For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.
For large amounts: Pump off product.

7. Handling and Storage

Handling

Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. Ensure adequate ventilation. No special measures necessary provided product is used correctly.

Protection against fire and explosion:
The product is not an oxidizer, not self-combustible and not explosive.

Storage

BASF Safety data sheet
 Date / Revised: 13.09.2017
 Product: **MasterProtect 1812 PART B**

Version: 2.0

(30667421/SDS_GEN_AU/EN)

Date of print 13.09.2017

Suitable materials for containers: Carbon steel (Iron), Stainless steel 1.4301 (V2), glass, tinned carbon steel (Tinplate)

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight. Store protected against freezing.

Storage stability:
 Storage temperature: 5 - 45 °C

Protect from temperatures below: 5 °C
 The packed product is destroyed at low temperatures or by frost.
 Protect from temperatures above: 45 °C
 The packed product will be damaged by high temperatures.

8. Exposure controls and personal protection

Components with occupational exposure limits

1,3-Benzenedimethanamine, 1477-55-0;

CLV 0.1 mg/m³ (ACGIHTLV)
 Skin Designation (ACGIHTLV)
 The substance can be absorbed through the skin.
 Skin Designation (AU NOEL)
 The substance can be absorbed through the skin.
 Peak limitation 0.1 mg/m³ (AU NOEL)
 Skin Designation (OEL (AU))
 The substance can be absorbed through the skin.
 Peak limitation 0.1 mg/m³ (OEL (AU))

Quartz (SiO₂), 14808-60-7;

TWA value 0.025 mg/m³ (ACGIHTLV), Respirable fraction (OEL (AU)), dust
 Included in the regulation, but with no data values - See the regulation for further details
 TWA value 0.1 mg/m³ (OEL (AU))
 TWA value 0.1 mg/m³ (AU NOEL), Respirable dust
 See Silica, Crystalline.
 TWA value 0.1 mg/m³ (AU NOEL), Respirable dust

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Combination filter for gases/vapours of organic, inorganic, acid inorganic and alkaline compounds (e.g. EN 14387 Type ABEK).

Hand protection:

Suitable chemical resistant safety gloves (EN 374) also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN 374): E.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), butyl rubber (0.7 mm) etc. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:
Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection:
Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:
Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Handle in accordance with good building materials hygiene and safety practice. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

9. Physical and Chemical Properties

Form:	viscous
Colour:	beige to light brown
Odour:	amine-like
pH value:	> 12 (20 °C)
Boiling point:	> 100 °C
Flash point:	> 100 °C
Flammability (solid/gas):	not flammable
Ignition temperature:	not determined
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.
Self ignition:	not self-igniting
Self heating ability:	It is not a substance capable of spontaneous heating.
Fire promoting properties:	not fire-propagating
Vapour pressure:	(20 °C) not applicable
Density:	1.4 g/cm ³ (20 - 23 °C)
Bulk density:	(20 °C) not applicable
Solubility in water:	not soluble

BASF Safety data sheet
Date / Revised: 13.09.2017
Product: **MasterProtect 1812 PART B**

Version: 2.0

(30667421/SDS_GEN_AU/EN)

Date of print 13.09.2017

Miscibility with water:
(20 °C)
immiscible
Hygroscopy: Non-hygroscopic
Viscosity, dynamic: No applicable information available.

Other Information:
If necessary, information on other physical and chemical parameters is indicated in this section.

10. Stability and Reactivity

Conditions to avoid:
See MSDS section 7 - Handling and storage.

Thermal decomposition: No decomposition if stored and handled as prescribed/indicated.

Substances to avoid:
acids, strong alkalies, aluminum compounds, zinc alloys, oxidizing agents

Corrosion to metals: No corrosive effect on metal.

Hazardous reactions:
The product is stable if stored and handled as prescribed/indicated.

Hazardous decomposition products:
No hazardous decomposition products if stored and handled as prescribed/indicated.

11. Toxicological Information

Acute toxicity

Assessment of acute toxicity:
Of moderate toxicity after short-term inhalation. Of moderate toxicity after single ingestion. Of low toxicity after short-term skin contact.

Irritation

Assessment of irritating effects:
Corrosive! Damages skin and eyes. May cause severe damage to the eyes.

Respiratory/Skin sensitization

Assessment of sensitization:
Sensitization after skin contact possible.

Germ cell mutagenicity

Assessment of mutagenicity:

(30667421/SDS_GEN_AU/EN)

Date of print 13.09.2017

The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity:

The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity:

The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Developmental toxicity

Assessment of teratogenicity:

The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Specific target organ toxicity (single exposure):

Assessment of STOT single:

Based on available Data, the classification criteria are not met.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

No reliable data was available concerning repeated dose toxicity. Based on available Data, the classification criteria are not met.

Aspiration hazard

No aspiration hazard expected.

Other relevant toxicity information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

12. Ecological Information

Ecotoxicity

Assessment of aquatic toxicity:

Very toxic to aquatic life with long lasting effects.

The product has not been tested. The statement has been derived from the properties of the individual components.

Mobility

Assessment transport between environmental compartments:

| No data available.

Persistence and degradability

Assessment biodegradation and elimination (H₂O):

| The polymer component of the product is poorly biodegradable.

Bioaccumulation potential

Assessment bioaccumulation potential:

| Discharge into the environment must be avoided.

Additional information

Other ecotoxicological advice:

| Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

13. Disposal Considerations

Observe national and local legal requirements.

Residues should be disposed of in the same manner as the substance/product.

Contaminated packaging:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

14. Transport Information

Domestic transport:

Hazard class:	8
Packing group:	II
ID number:	UN 3267
Hazard label:	8, EHSM
Proper shipping name:	CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (contains M-PHENYLENEBIS(METHYLAMINE), FORMALDEHYDE, POLYMER WITH BENZENEDIMETHANAMINE + PHENOL)

Further information

Hazchem Code:2X

IERG Number:36

Sea transport

IMDG

| Hazard class: 8

BASF Safety data sheet
 Date / Revised: 13.09.2017
 Product: **MasterProtect 1812 PART B**

Version: 2.0

(30667421/SDS_GEN_AU/EN)

Date of print 13.09.2017

Packing group:	II
ID number:	UN 3267
Hazard label:	8, EHSM
Marine pollutant:	YES
Proper shipping name:	CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (contains M-PHENYLENEBIS(METHYLAMINE), FORMALDEHYDE, POLYMER WITH BENZENEDIMETHANAMINE + PHENOL)

Air transport

IATA/ICAO

Hazard class:	8
Packing group:	II
ID number:	UN 3267
Hazard label:	8
Proper shipping name:	CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (contains M-PHENYLENEBIS(METHYLAMINE), FORMALDEHYDE, POLYMER WITH BENZENEDIMETHANAMINE + PHENOL)

15. Regulatory Information**Other regulations**

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP): Schedule 5

Registration status:

AICS, AU released / listed

16. Other Information

Vertical lines in the left hand margin indicate an amendment from the previous version.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.