

Safety data sheet

Page: 1/9

BASF Safety data sheet

Date / Revised: 17.01.2016

Product: **MasterSeal M 882 Grey PART B**

Version: 1.0

(30654781/SDS_GEN_AU/EN)

Date of print 18.01.2016

1. Substance/preparation and manufacturer/supplier identification

MasterSeal M 882 Grey PART B

Use: Product for construction chemicals

Manufacturer/supplier:

BASF Australia Limited (ABN 62 008 437 867)

Level 12, 28 Freshwater Place Southbank

Victoria 3006, AUSTRALIA

Telephone: +61 3 8855-6600

Telefax number: +61 3 8855-6511

Emergency information:

BASF Emergency Advice Number: 1800 803 440 (24h) [within Australia]

BASF Emergency Advice Number: + 61 3 8855 6666 [outside Australia]

2. Hazard identification

Classification of the substance and mixture:

Skin corrosion/irritation: Cat. 1B

Serious eye damage/eye irritation: Cat. 1

Skin sensitization: Cat. 1B

Hazardous to the aquatic environment - acute: Cat. 3

Hazardous to the aquatic environment - chronic: Cat. 3

Label elements and precautionary statement:

Pictogram:



BASF Safety data sheet
Date / Revised: 17.01.2016
Product: **MasterSeal M 882 Grey PART B**

Version: 1.0

(30654781/SDS_GEN_AU/EN)

Date of print 18.01.2016

Signal Word:
Danger

Hazard Statement:

May cause an allergic skin reaction. Causes severe skin burns and eye damage. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust or mist. Avoid release to the environment. Contaminated work clothing should not be allowed out of the workplace. Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Storage):

Store locked up.

Precautionary Statements (Disposal):

Dispose of contents/container to hazardous or special waste collection point.

Other hazards which do not result in classification:

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

3. Composition/information on ingredients

Chemical nature

Preparation based on: polyamine

Hazardous ingredients

Cyclohexanemethanamine, 1,3,3-trimethyl-N-(2-methylpropylidene)-5-((2-methylpropylidene)amino)-

Content (W/W): >= 5 % - < 15 %	Skin Corr./Irrit.: Cat. 1B
CAS Number: 54914-37-3	Skin Sens.: Cat. 1
	Aquatic Chronic: Cat. 3

Aspartic acid, N,N'-(methylenedi-4,1-cyclohexanediyl)bis-, tetraethyl ester

Content (W/W): >= 60 % - <= 100 %	Skin Corr./Irrit.: Cat. 3
	Skin Sens.: Cat. 1
CAS Number: 136210-30-5	Aquatic Acute: Cat. 3
	Aquatic Chronic: Cat. 3

4. First-Aid Measures

General advice:

First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

On skin contact:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Rinse mouth immediately and then drink plenty of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.

Note to physician:

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Suitable extinguishing media:

foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:

water jet

Specific hazards:

carbon dioxide, carbon monoxide, nitrogen oxides, fumes/smoke, carbon black, corrosive gases/vapours

Special protective equipment:

Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental Release Measures

Personal precautions:

Use personal protective clothing. Do not breathe vapour/aerosol/spray mists. Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions:

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods for cleaning up or taking up:

For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.

For large amounts: Pump off product.

7. Handling and Storage

Handling

Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. Ensure adequate ventilation. No special measures necessary provided product is used correctly.

Protection against fire and explosion:

The product does not contribute to the spreading of flames, nor is it self combustible, not explosive.

Storage

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight. Store protected against freezing.

The packed product is not damaged by low temperatures or by frost.

The packed product will not be damaged by high temperatures.

8. Exposure controls and personal protection

Components with occupational exposure limits

No occupational exposure limits known.

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Combination filter for gases/vapours of organic, inorganic, acid inorganic and alkaline compounds (e.g. EN 14387 Type ABEK).

Hand protection:

Suitable chemical resistant safety gloves (EN 374) also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN 374): E.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), butyl rubber (0.7 mm) etc. Manufacturer's directions for use should be observed because of great diversity of types.

BASF Safety data sheet
Date / Revised: 17.01.2016
Product: **MasterSeal M 882 Grey PART B**

Version: 1.0

(30654781/SDS_GEN_AU/EN)

Date of print 18.01.2016

Eye protection:
Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection:
Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:
Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Handle in accordance with good building materials hygiene and safety practice. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

9. Physical and Chemical Properties

Form:	liquid
Colour:	various, depending on the colourant
Odour:	Unspecified
pH value:	Unspecified
Boiling point:	Unspecified
Flash point:	not available
Ignition temperature:	Unspecified
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.
Self ignition:	Unspecified
Fire promoting properties:	Unspecified
Vapour pressure:	(20 °C) Unspecified
Density:	1.04 g/cm ³ (20 °C) not available
Bulk density:	(20 °C) Unspecified
Solubility in water:	not available
Miscibility with water:	(20 °C)

BASF Safety data sheet
Date / Revised: 17.01.2016
Product: **MasterSeal M 882 Grey PART B**

Version: 1.0

(30654781/SDS_GEN_AU/EN)

Date of print 18.01.2016

Other Information:

If necessary, information on other physical and chemical parameters is indicated in this section.

10. Stability and Reactivity**Conditions to avoid:**

See MSDS section 7 - Handling and storage.

Thermal decomposition: No decomposition if stored and handled as prescribed/indicated.

Substances to avoid:

zinc, aluminium, oxidizing agents, strong alkalies, acids

Corrosion to metals: No data available.

Hazardous reactions:

The product is stable if stored and handled as prescribed/indicated.

Hazardous decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

11. Toxicological Information**Acute toxicity****Assessment of acute toxicity:**

Virtually nontoxic after a single ingestion. Based on available Data, the classification criteria are not met.

Irritation**Assessment of irritating effects:**

Corrosive! Damages skin and eyes. May cause severe damage to the eyes.

Respiratory/Skin sensitization**Assessment of sensitization:**

Sensitization after skin contact possible.

Germ cell mutagenicity**Assessment of mutagenicity:**

The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity:

The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity:

The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Developmental toxicity

Assessment of teratogenicity:

The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

No reliable data was available concerning repeated dose toxicity. Based on available Data, the classification criteria are not met.

Other relevant toxicity information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

12. Ecological Information

Ecotoxicity

Assessment of aquatic toxicity:

Acutely harmful for aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Mobility

Assessment transport between environmental compartments:

No data available.

Persistence and degradability

Assessment biodegradation and elimination (H₂O):

The polymer component of the product is poorly biodegradable.

Bioaccumulation potential

Assessment bioaccumulation potential:

Discharge into the environment must be avoided.

Additional information

BASF Safety data sheet
 Date / Revised: 17.01.2016
 Product: **MasterSeal M 882 Grey PART B**

Version: 1.0

(30654781/SDS_GEN_AU/EN)

Date of print 18.01.2016

Other ecotoxicological advice:

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

13. Disposal Considerations

Observe national and local legal requirements.

Residues should be disposed of in the same manner as the substance/product.

Contaminated packaging:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

14. Transport Information

Domestic transport:

Hazard class:	8
Packing group:	II
ID number:	UN 2735
Hazard label:	8
Proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (contains 1,3,3-TRIMETHYL-N-(2-METHYLPROPYLIDENE)-5-[(2-METHYLPROPYLIDENE)AMINO]CYCLOHEXANEMETHYLAMINE)

Further information

Hazchem Code:2X

IERG Number:36

Sea transport

IMDG

Hazard class:	8
Packing group:	II
ID number:	UN 2735
Hazard label:	8
Marine pollutant:	NO
Proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (contains 1,3,3-TRIMETHYL-N-(2-METHYLPROPYLIDENE)-5-[(2-METHYLPROPYLIDENE)AMINO]CYCLOHEXANEMETHYLAMINE)

Air transport

IATA/ICAO

Hazard class:	8
Packing group:	II
ID number:	UN 2735
Hazard label:	8

BASF Safety data sheet
Date / Revised: 17.01.2016
Product: **MasterSeal M 882 Grey PART B**

Version: 1.0

(30654781/SDS_GEN_AU/EN)

Date of print 18.01.2016

Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (contains 1,3,3-
TRIMETHYL-N-(2-METHYLPROPYLIDENE)-5-[(2-
METHYLPROPYLIDENE)AMINO]CYCLOHEXANEMETHYLAMINE
)

15. Regulatory Information

Other regulations

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP): Not Scheduled

Registration status:

AICS, AU released / listed

16. Other Information

Vertical lines in the left hand margin indicate an amendment from the previous version.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. The data do not describe the product's properties (product specification). Neither should any agreed property nor the suitability of the product for any specific purpose be deduced from the data contained in the safety data sheet. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.