

Safety data sheet

Page: 1/9

BASF Safety data sheet
Date / Revised: 05.06.2015
Product: **MasterSeal P 692**

Version: 1.0

(30643513/SDS_GEN_AU/EN)

Date of print 05.06.2015

1. Substance/preparation and manufacturer/supplier identification

MasterSeal P 692

Use: Product for construction chemicals

Manufacturer/supplier:

BASF Australia Limited (ABN 62 008 437 867)
Level 12, 28 Freshwater Place Southbank
Victoria 3006, AUSTRALIA
Telephone: +61 3 8855-6600
Telefax number: +61 3 8855-6511

Emergency information:

BASF Emergency Advice Number: 1800 803 440 (24h) [within Australia]
BASF Emergency Advice Number: + 61 3 8855 6666 [outside Australia]

2. Hazard identification

Classification of the substance and mixture:

Aspiration hazard: Cat. 1

Acute toxicity: Cat. 4 (Inhalation - vapour)

Skin corrosion/irritation: Cat. 2

Serious eye damage/eye irritation: Cat. 2A

Respiratory sensitization: Cat. 1

Skin sensitization: Cat. 1

Carcinogenicity: Cat. 2

Specific target organ toxicity — single exposure: Cat. 3 (irritating to respiratory system)

Specific target organ toxicity — repeated exposure: Cat. 2

Label elements and precautionary statement:

Pictogram:



Signal Word:
Danger

Hazard Statement:

Causes serious eye irritation. Causes skin irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May be fatal if swallowed and enters airways. May cause damage to organs through prolonged or repeated exposure. May cause respiratory irritation. Suspected of causing cancer.

Precautionary Statements (Prevention):

Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust/gas/mist/vapours. Obtain special instructions before use. Avoid breathing vapours. Do not handle until all safety precautions have been read and understood. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

IF exposed or concerned: Call a POISON CENTER or doctor/physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Get medical advice/attention if you feel unwell. IF ON SKIN (or hair): Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Precautionary Statements (Storage):

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Precautionary Statements (Disposal):

Dispose of contents/container to hazardous or special waste collection point.

Other hazards which do not result in classification:

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

BASF Safety data sheet
Date / Revised: 05.06.2015
Product: **MasterSeal P 692**

Version: 1.0

(30643513/SDS_GEN_AU/EN)

Date of print 05.06.2015

3. Composition/information on ingredients

Chemical nature

Hazardous ingredients

Diphenylmethane-4,4'-diisocyanate (MDI)

Content (W/W): $\geq 25\%$ - $< 50\%$

CAS Number: 101-68-8

Acute Tox.: Cat. 4 (Inhalation - mist)

Skin Corr./Irrit.: Cat. 2

Eye Dam./Irrit.: Cat. 2B

Resp. Sens.: Cat. 1

Skin Sens.: Cat. 1B

Carc.: Cat. 2

STOT SE: Cat. 3 (irr. to respiratory syst.)

STOT RE (Respiratory system): Cat. 2 (by inhalation)

Solvent naphtha (petroleum), heavy arom.

Content (W/W): $\geq 25\%$ - $< 50\%$

CAS Number: 64742-94-5

Asp. Tox.: Cat. 1

4. First-Aid Measures

General advice:

First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

On skin contact:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Rinse mouth immediately and then drink plenty of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.

Note to physician:

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Suitable extinguishing media:
foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:
water jet

Specific hazards:
carbon dioxide, carbon monoxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

Special protective equipment:
Wear a self-contained breathing apparatus.

Further information:
The degree of risk is governed by the burning substance and the fire conditions. If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental Release Measures

Personal precautions:
Do not breathe vapour/aerosol/spray mists. Wear eye/face protection. If exposed to high vapour concentration, leave area immediately. Use personal protective clothing. Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions:
Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods for cleaning up or taking up:
For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.
For large amounts: Pump off product.

7. Handling and Storage

Handling

Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. No special measures necessary provided product is used correctly.

Storage

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight.

The packed product is not damaged by low temperatures or by frost.
The packed product will not be damaged by high temperatures.

8. Exposure controls and personal protection

Components with occupational exposure limits

Diphenylmethane-4,4'-diisocyanate (MDI), 101-68-8;
STEL value 0.07 mg/m³ (OEL (AU))
TWA value 0.02 mg/m³ (OEL (AU))
TWA value 0.02 mg/m³ (AU NOEL)
STEL value 0.07 mg/m³ (AU NOEL)
STEL value 0.07 mg/m³ (AU NOEL)
TWA value 0.02 mg/m³ (AU NOEL)
TWA value 0.005 ppm (ACGIHTLV)

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Combination filter for gases/vapours of organic, inorganic, acid inorganic and alkaline compounds (e.g. EN 14387 Type ABEK).

Hand protection:

Suitable chemical resistant safety gloves (EN 374) also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN 374): E.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), butyl rubber (0.7 mm) etc. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures:

Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

9. Physical and Chemical Properties

Form: liquid
Colour: amber
Odour: Unspecified

pH value: Unspecified

BASF Safety data sheet
Date / Revised: 05.06.2015
Product: **MasterSeal P 692**

Version: 1.0

(30643513/SDS_GEN_AU/EN)

Date of print 05.06.2015

Boiling point:	Unspecified
Flash point:	not available
Ignition temperature:	Unspecified
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.
Self ignition:	Unspecified
Fire promoting properties:	Unspecified
Vapour pressure:	(20 °C) Unspecified
Density:	1.00 - 1.02 g/cm ³ (20 °C)
Bulk density:	(20 °C) Unspecified
Solubility in water:	not available
Miscibility with water:	(20 °C)
Solids content:	43 - 47 %

Other Information:

If necessary, information on other physical and chemical parameters is indicated in this section.

10. Stability and Reactivity

Conditions to avoid:

See MSDS section 7 - Handling and storage.

Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.
------------------------	---

Substances to avoid:

strong acids, strong bases, strong oxidizing agents, strong reducing agents

Corrosion to metals: No data available.

Hazardous reactions:

The product is stable if stored and handled as prescribed/indicated.

No hazardous decomposition products if stored and handled as prescribed/indicated.

11. Toxicological Information

Acute toxicity

Assessment of acute toxicity:
Of moderate toxicity after short-term inhalation.

Irritation

Assessment of irritating effects:
Eye contact causes irritation. Skin contact causes irritation.

Respiratory/Skin sensitization

Assessment of sensitization:
The substance may cause sensitization of the respiratory tract. Sensitization after skin contact possible.

Germ cell mutagenicity

Assessment of mutagenicity:
The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity:
Indication of possible carcinogenic effect in animal tests.

Reproductive toxicity

Assessment of reproduction toxicity:
The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Developmental toxicity

Assessment of teratogenicity:
The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Contains isocyanates. Observe manufacturer's instructions.

Specific target organ toxicity (single exposure):

Assessment of STOT single:
Causes temporary irritation of the respiratory tract.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:
Repeated exposure may affect certain organs.

Aspiration hazard

May also damage the lung at swallowing (aspiration hazard).

Other relevant toxicity information

The product has not been tested. The statement has been derived from the properties of the individual components.

12. Ecological Information

Ecotoxicity

Assessment of aquatic toxicity:
Based on available Data, the classification criteria are not met. There is a high probability that the product is not acutely harmful to aquatic organisms.

Mobility

Assessment transport between environmental compartments:
No data available.

Persistence and degradability

Assessment biodegradation and elimination (H₂O):
The polymer component of the product is poorly biodegradable.

Bioaccumulation potential

Assessment bioaccumulation potential:
Discharge into the environment must be avoided.

Additional information

Other ecotoxicological advice:
Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

13. Disposal Considerations

Observe national and local legal requirements.
Residues should be disposed of in the same manner as the substance/product.

Contaminated packaging:
Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

BASF Safety data sheet
Date / Revised: 05.06.2015
Product: **MasterSeal P 692**

Version: 1.0

(30643513/SDS_GEN_AU/EN)

Date of print 05.06.2015

14. Transport Information

Domestic transport:

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Other regulations

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP): Not Scheduled

Registration status:

AICS, AU

released / listed

16. Other Information

Vertical lines in the left hand margin indicate an amendment from the previous version.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. The data do not describe the product's properties (product specification). Neither should any agreed property nor the suitability of the product for any specific purpose be deduced from the data contained in the safety data sheet. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.