

	Scratchcoat	Smooth texture R11	Non-slip texture R12	Non-slip texture R 13	Wet pendulum slip rating S55 rubber	Heavy impact resistance	High temperature resistance 80C	High temperature resistance 90C	High temperature resistance 120C	Non-taint	Calcined bauxite filler to get R11	Calcined bauxite filler to get R12	Calcined bauxite filler to get R13	8 hour cure at 5C	8 hour cure at 20C	Chemical resistance to organic acids	Chemical resistance to inorganic acids	Chemical resistance to solvents	Chemical resistance to alkalis	Tracked vehicles	Cool rooms	Colour pack	Topcoat	Material
Ucrete® MF/B4	X	X			P4		X (6mm)			X					X	X	X	X	X		X	X	B4	Polyurethane cement
Ucrete® UD 200			X		P5	X		X	X	X					X	X	X	X	X		X	X		Polyurethane cement
Ucrete® DP 10		X			P5		X	X	X	X					X	X	X	X	X		X	X	X	Polyurethane cement
Ucrete® DP 20			X	X	P5		X	X	X	X					X	X	X	X	X		X	X	X	Polyurethane cement
Ucrete® DP 30				X	P5		X	X	X	X					X	X	X	X	X		X	X	X	Polyurethane cement
Ucrete® IF				X	P5	X	X	X	X	X					X	X	X	X	X	X	X	X		Polyurethane cement
Ucrete® Fast							X	X	X	X				X		X	X	X	X		X			Polyol
Ucrete® B6								X		X					X	X	X	X	X					Polyurethane cement
Ucrete® B9						X	X		X	X					X	X	X	X	X					Polyurethane cement
Ucrete® Filler F10		X									X													Calcined bauxite
Ucrete® Filler F20												X	X											Calcined bauxite
Ucrete® Filler F25													X											Calcined bauxite