

DECLARATION OF PERFORMANCE Nr. BE0003/01

according Annex III of the Regulation (EU) No 305/2011

MasterProtect H 303

1. Unique identification code of the product-type:

EN 1504-2 Methods 1.1/2.1/8.1

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

batch number: see packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Water based, hydrofobic agent for concrete

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

BASF Belgium Coordination Center Comm.V.
Business Belux – Construction
Nijverheidsweg 89 – Industrieterrein Ravenshout/nr.3711
B – 3945 Ham
Tel.: +32 (0) 11 34 04 34
Fax.: +32 (0) 11 40 13 92
basf-cc-be@basf.com - www.basf-cc.be

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

system 2+

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The notified body : BCCA
Rue d'Arlon 53
B – 1040 BRUSSELS(identification number 0749), performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued: 0749-CPD-BC2-562-0013-0005-001 Certificate of conformity of the factory production control.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not relevant

9. Declared performance (MasterProtect H 303)

Essential Characteristics	Performance	Harmonised technical specification EN 1504-2 : 2004
Resistance against freeze-thaw salt stress of impregnated hydrofobic concrete (determination of loss of mass)	NPD	
Penetration depth	Class I	
Water absorption and alkali resistance	Pass	
Drying rate for hydrofobic impregnation	Class I	
Dangerous substances	Comply with 5.3 (EN 1504-2)	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Christoph de Monie
Site Manager Ham &
Supply chain manager EBE for Benelux



Richard Webers
Technical Manager

Ham, 20.06.2013