


MasterSeal[®] 949

TPO flat metal strip

DESCRIPTION

Finishing element for TPO membrane. Zinc steel strip coated on the surface with TPO membrane resistant to weathering and ultraviolet rays.



PRIMARY USE

MasterSeal 949 is designed to be used as an accessory for termination and fixing element in the TPO membranes waterproofing systems from BASF.

PACKAGING

MasterSeal 949 is supplied in a packing of 10 pc per box.

Thickness	1.8mm
Height	40mm
Length	2m / 3 m
Weight	0.27kg/m
Colour	Sand Grey

TYPICAL PROPERTIES*

Puncture resistance DIN 16726-5.12	≥400mm
Cold bending DIN 53361	≤ -35°C
Resistance to artificial weathering DIN 16726-5.17	No weathering

APPLICATION PROCEDURE

For application details, please refer to the TPO membrane system method statement / manual or contact BASF Technical Services department.

NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local BASF Construction Chemicals representative.

BASF reserves the right to have the true cause of any liability determined by accepted test methods.

QUALITY AND CARE

All products originating from BASF's Dubai, UAE facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational Health & Safety standards ISO 9001, ISO 14001 and ISO 45001.

* Properties listed are based on laboratory controlled tests.

® = Registered trademark of the BASF-Group in many countries.



We create chemistry

MasterSeal[®] 949

BASF_CC-UAE/SI_949_03_18/v1/

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this BASF publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by BASF either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not BASF, are responsible for carrying out procedures appropriate to a specific application.

BASF Construction Chemicals UAE LLC
P.O. Box 37127, Dubai, UAE
Tel: +971 4 8090800, Fax: +971 4 8851002
www.master-builders-solutions.basf.ae

Disclaimer: the LRQA mark relates to certified management system and not to the product mentioned on this datasheet



MASTER[®]
» BUILDERS
SOLUTIONS