

MasterSeal[®] P 101

Universal modified silane primer for use with MasterSeal series sealants

DESCRIPTION

A liquid primer used in the preparation of joint surfaces prior to the use of **MasterSeal** range of sealants.

MasterSeal P 101 is used when preparing porous surfaces such as concrete, brickwork, stonework, asbestos and timber and non-porous surfaces such as stainless steel and ceramics.

PACKAGING

MasterSeal P 101 is available in 750-ml tins.

APPLICATION TEMPERATURE

5°C to 40°C.

COVERAGE

Theoretical coverage approx. 20m² per litre.

WATCHPOINT

Due to the penetrating and sealing action of **MasterSeal P 101**, staining may occur on materials such as granite, marble, natural stone and man made composites. If in doubt consult BASF's Technical Services Department.

DIRECTIONS FOR USE

PREPARATION OF SURFACES

Joint faces to be primed must be completely dry and free from all dirt, dust, cement laitance and other loose and deleterious matter. This is best achieved by grit or sand blasting or thorough wire brushing and then blowing clean with oil free compressed air.

APPLICATION

Pour a small amount of the primer into a clean container ensuring that the main container is tightly resealed. Liberally apply a coat of primer with a soft brush to the required surface. Allow to become tack free before installing **MasterSeal** sealants. If primer is left for more than 3 hours re-priming is necessary.

Note: **MasterSeal** primers are solvent-based.

EQUIPMENT CARE

Clean all brushes immediately with a suitable Xylene thinners.

SAFETY PRECAUTIONS

Flammable or highly flammable liquids. Do not apply when smoking or near naked flame. Wear protective gloves and goggles. Use in well ventilated areas and avoid breathing of vapour.

In the event of narcosis by inhalation of concentrated vapour, remove person to fresh air and call for medical attention. If in contact with eyes, irrigate thoroughly for at least five minutes with clean, cold water and seek medical attention.

In the event of a fire, extinguish with carbon dioxide, dry chemical or foam fire extinguisher.

STORAGE

Store under cover out of direct sunlight and protect from extremes of temperature. In tropical climates the product must be stored in an air conditioned environment.

Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage advice consult BASF's Technical Services Department.

MasterSeal[®] P 101

NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local BASF representative.

BASF reserves the right to have the true cause of any difficulty determined by accepted test methods.

QUALITY AND CARE

All products originating from BASF's Dubai, UAE facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001 and ISO 45001.

® = Registered trademark of the BASF-Group in many countries.

BASF_CC-UAE/SI_P_101_04_03/v2/07_14

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this BASF publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by BASF either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not BASF, are responsible for carrying out procedures appropriate to a specific application.