

Specification Clause

MasterTile® 530

Description

MasterTile 530 is a fine coloured latex modified powder which, when mixed with water, gives a smooth, easily applied creamy paste for clean grouting of ceramic tiles. It sets to a decorative water resistant finish.

Where indicated on the contract documents the latex modified cement grout for ceramic, glass mosaic, porcelain and non-moisture sensitive natural stones tiles shall be **MasterTile 530** manufactured by BASF Construction Chemicals UAE LLC.

The product shall meet or exceed the following performance criteria:

Testing	Standard	Result
ANSI Specifications for Polymer Modified Cement Grouts for Tile Installation	A118.7	Complies
Testing of Cementitious Grout for Tile	DIN EN 13888-2009-08	All requirements fulfilled for CG2
Pull Off Test	BS EN 1542: 1999	>1.5N/mm ²
Compressive Strength	BS EN 1015-11	>40N/mm ²
Volatile Organic Content	SCAQMD	<5g/L

Standards

BS 5980 - Cementitious Adhesives and Grouts, ANSI 118.7 (Polymer Modified Cement Grouts), BS EN 13888 CG2

The product shall be manufactured by a company certified to confirm to the requirements of the quality, environmental and occupational health & safety standards of ISO 9001, ISO 14001 and ISO 45001

The technical information and application advice given in this BASF publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

For additional information please consult the product Technical Data Sheet.

BASF Construction Chemicals UAE LLC can provide a full project specification and method statement on request.