

Specification Clause

MasterTile® WP Tape

Description

Special waterproofing tape system for waterproof corner and perimeter joints, pipe culverts and floor drains.

Where indicated on the contract documents the waterproofing tape system for waterproof corner and perimeter joints, pipe culverts and floor drains shall be **MasterTile WP Tape** manufactured by BASF Construction Chemicals UAE LLC.

The product shall meet or exceed the following performance criteria:

Testing	Standard	Result
Tear-out force extensibility diagonal		> 15 Mpa
Elongation at break extensibility diagonal		> 200%
Temperature resistance in service		-20°C to +80°C
Volatile Organic Compounds (VOC)	SCAQMD	44g/m ²

Standards

ZDB leaflet "Bonded waterproofing", edition 2005.

Building regulation list A part 2 no. 1.10 "Waterproofing substances to be applied in liquid condition directly under tiles

The product shall be manufactured by a company certified to confirm to the requirements of the quality, environmental and occupational health & safety standards of ISO 9001, ISO 14001 and ISO 45001

The technical information and application advice given in this BASF publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

For additional information please consult the product Technical Data Sheet.

BASF Construction Chemicals UAE LLC can provide a full project specification and method statement on request.