

## Specification Clause

### Wabo<sup>®</sup>crete II AE

#### Description

**Wabocrete II AE** is a three-part polyurethane mortar. Part A is a low-viscosity clear liquid; Part B is a low-viscosity brown liquid; Part C is blend of aggregate and fine reactive powders.

Where indicated on the contract documents the solvent-free polyurethane mortar for expansion joint shall be **Wabocrete II AE** manufactured by BASF Construction Chemicals UAE LLC.

The product shall meet or exceed the following performance criteria:

Testing	Standard	Results
Compressive strength - 14 days	ASTM C579	>10N/mm <sup>2</sup>
Tensile strength	ASTM D638	>3N/mm <sup>2</sup>
Bond to concrete - 7 days	ASTM D4541	>1.8N/mm <sup>2</sup>
Volatile Organic Compounds (VOC)	SCAQMD	<5g

**The product shall be manufactured by a company certified to conform to the requirements of the quality, environmental and occupational health & safety standards of ISO 9001, ISO 14001 and ISO 45001**

The technical information and application advice given in this BASF publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

For additional information please consult the product Technical Data Sheet.

BASF Construction Chemicals UAE LLC can provide a full project specification and method statement on request.