

MasterKure[®] 181SW

Silane siloxane resin based multi-role curing, sealing, priming & impregnating protective treatment for concrete

DESCRIPTION

MasterKure 181SW is a non-degrading, membrane-forming liquid based on silane siloxane resin suitable for spray application to freshly poured concrete.

The resultant film retains sufficient moisture in the concrete to ensure full hydration of the cement; essential for optimum strength development. The cured concrete is typically harder and exhibits a dust free surface with a reduced incidence of drying shrinkage cracks.

Additionally, the membrane acts as a primer system for many subsequent surface finishes that do not rely on penetration for substrate bond.

When applied to floors, the **MasterKure 181SW** seals and dustproofs the surface, eliminating the primary source of abrasion and enhancing durability.

TYPICAL APPLICATIONS

As a more effective and economical alternative to separate curing and priming/sealing regimes. Suitable for use on all concrete surfaces.

- Surfaces subject to finishing treatments.
- Economical enhancement of concrete flatwork.
- In high-rise construction to eliminate the requirement for water curing.

ADVANTAGES

- Eliminates the need for water curing.
- Penetrative protective treatment
- Imparts a harder dust free surface.
- Non degrading, acts as a primer system.
- Minimal delay for overcoating etc.
- Abrasion resistant floors.
- Water repellent concrete
- High curing efficiency.
- Reduced labour costs.
- Reduces chloride penetration.

PACKAGING

MasterKure 181SW is available in 210 litre drums.

TYPICAL PROPERTIES*

Appearance:	White liquid
Specific gravity:	0.875 at 25°C
Flashpoint:	35°C (PMCC)
Finished film appearance:	White, tack free, water repellent film

STANDARDS

ASTM C309 Type II Class B

DIRECTIONS FOR USE

The compound should be spray applied as evenly as possible to the freshly placed concrete.

For horizontal surfaces the **MasterKure 181SW** should be applied as soon as the initial surface sheen has disappeared from the concrete face. In the case of formed concrete, the product should be applied immediately on removal of the formwork.

COVERAGE

The recommended rate of application is 4.5 to 5.5 square metres per litre. This corresponds to that at which **MasterKure 181SW** has been tested, and at which it attains the claimed degree of curing efficiency. In favourable conditions such as shaded interior surfaces, adequate curing can be achieved with extended coverage rates.

When using **MasterKure 181SW** for floor areas where maximum chemical and wear resistance is required, it is recommended that a further coat be applied after 24 hours.

A single coat application is adequate when used as a primer system for coatings.

MasterKure® 181SW

SUBSEQUENT SURFACE FINISHES

The resin in **MasterKure 181SW** ensure that bond is maintained with adhesives used for installing tiles, and other floor coverings.

MasterKure 181SW will act as a primer for paint systems and will enable most surface treatments to progress with minimal delay.

Typical surface treatments that will bond to surfaces with **MasterKure 181SW** are:

- Water based emulsion paints containing PVA, PVC or acrylic co-polymers.
- Tile adhesives based on the above polymers.
- Bituminous emulsions and solutions.
- Polymer modified cement systems.
- Polyurethane resin systems.
- Polysulphide systems.

For further information regarding compatibility of **MasterKure 181SW**, contact BASF UAE's Technical Services Department.

SPECIFICATION CLAUSE

Where indicated, concrete shall be cured by application of **MasterKure 181SW**, curing compound based on acrylic resin manufactured by BASF UAE or similar approved; to the following specification:

Specification type ASTM C309: Type II Class B

MasterKure 181SW is to be applied at a coverage rate of 4.5 to 5.5 square metres per litre and strictly in accordance with the manufacturer's instructions.

STORAGE

Store under cover, out of direct sunlight and protect from extremes of temperature.

Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage advice consult BASF's Technical Services Department.

SAFETY PRECAUTIONS

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs. Treat splashes to eyes and skin immediately. If accidentally ingested, seek medical attention. Reseal containers after use. Use in well ventilated areas and avoid inhalation. For further information refer to the material safety data sheet.

NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local BASF representative.

BASF reserves the right to have the true cause of any difficulty determined by accepted test methods.

QUALITY AND CARE

All products originating from BASF's Dubai, UAE facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001 and OHSAS 18001.

* Properties listed are based on laboratory controlled tests.

® = Registered trademark of the BASF-Group in many countries.

BASF_CC-UAE/Kure_181SW_12_94/v3/03_16

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this BASF publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by BASF either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not BASF, are responsible for carrying out procedures appropriate to a specific application.