

# MasterProtect<sup>®</sup> FL 200

## Ready mixed blow hole filler for internal surfaces

### DESCRIPTION

**MasterProtect FL 200** is a ready-mixed, pre-bagged blend of acrylic polymers and graded fillers for re-levelling and refurbishment of most internal building surfaces, prior to over coating.

### ADVANTAGES

- Easy to apply.
- Does not flake off or de-laminate.
- Good adhesion.
- Minimal shrinkage
- Quick drying.
- Vapour permeable.

### AREA OF USE

When dry, **MasterProtect FL 200** bonds extremely well to cementitious materials, gypsum boards, spray plasters and gypsum.

### PACKAGING

**MasterProtect FL 200** is supplied in 25kg units.

### TYPICAL PROPERTIES

Binders	Acrylic copolymer
Fillers	Fine precisely graded fillers
Specific gravity	1.70 ±0.05
Toxicity	Non-toxic
Colour	White

### PREPARATION OF SURFACE

Ensure that the surface is free from dust, dirt, form oil and contamination. Ridges and undulations must also be removed.

N.B. The use of penetrating primer is recommended on dusting or flaking surfaces, for further information contact BASF UAE Technical Department.

### APPLICATION & CLEANING TOOLS

Apply the filler in a thin, even layer; if the area under repair requires a thick coat. Apply several thin layers, allowing each layer to dry before adding the next.

Lightly sandpaper over the dry final surface before painting preferably within 9 hours of application.

Clean tools and equipment with water after use.

### COVERAGE

Apply the filler in a thin even layer between 0.2-0.4kg/m<sup>2</sup> (dependent on substrate conditions). Apply multiple coats if necessary, allowing to dry between layers. Lightly sand down the final surface before overcoating within 24 hours of application. Applied material must not exceed 1mm per coat.

### STORAGE AND SHELF LIFE

Store bags in a clean dry area protected from direct sunlight and extreme heat and cold.

Shelf life is 12 months, in original unopened packaging.

### HEALTH AND SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

### NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local BASF representative.

BASF reserves the right to have the true cause of any difficulty determined by accepted test methods.



We create chemistry

# MasterProtect<sup>®</sup> FL 200

---

## QUALITY AND CARE

All products originating from BASF's Dubai, UAE facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001 and OHSAS 18001

® = Registered trademark of the BASF-Group in many countries.

BASF\_CC-UAE/Pr\_FL200\_02\_05/v2/07\_16

### STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this BASF publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

### NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by BASF either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not BASF, are responsible for carrying out procedures appropriate to a specific application.

**BASF Construction Chemicals UAE LLC**  
P.O. Box 37127, Dubai, UAE  
Tel: +971 4 8090800, Fax: +971 4 8851002  
[www.master-builders-solutions.basf.ae](http://www.master-builders-solutions.basf.ae)

**Disclaimer:** the LRQA mark relates to certified management system and not to the product mentioned on this datasheet



**MASTER<sup>®</sup>**  
**BUILDERS**  
SOLUTIONS