

MasterRoc[®] EPB 11

Multi-purpose EP2 grease for Tunnel Boring Machines (TBM)

DESCRIPTION

MasterRoc EPB 11 is a multi-purpose lithium thickened EP2 grade grease designed for main bearing lubrication, as a screw conveyor drive assembly grease and as a rotary swivel grease.

FEATURES AND BENEFITS

- Contains antioxidants, corrosion inhibitors and EP/AW additives.
- Offers good mechanical stability, load carrying capacity and corrosion protection, which makes it suitable for loaded bearings as well as wet environments.
- High quality multipurpose grease suitable for a wide range of plain and rolling bearings.

PACKAGING

MasterRoc EPB 11 is available in 180kg steel drums for press plate pumps.

TECHNICAL DATA*

Form	Homogenous paste
Colour	Yellowish-brown
NLGI Grade	2
Density [kg/m³] 20°C	Approx. 950
Consistency ISO 2137 [1/10 mm]	265-295
4-ball wear DIN 51350:5 [mm]	0.5
Base oil viscosity (40°C) ISO 12058	200 mm ² /s
Base oil viscosity (100°C) ISO 12058	15 mm ² /s
Temperature range	-30°C to 120°C
4 ball weld load DIN 51350:4	2600 N
Lubricating Ability SKF R2F test A + B	Pass
Water resistance DIN 51807/1	0-90
Flash point (base oil)	> 150°C

STORAGE

MasterRoc EPB 11 should be stored at 5 - 35°C. If stored in original tightly closed drums it has a shelf life of 12 months.

SAFETY PRECAUTIONS

MasterRoc EPB 11 is not hazardous and poses no threat to worker safety or the environment. However, it is recommended that all normal precautions be taken when handling the product, such as the use of eye protection and gloves.

* Properties listed are based on laboratory controlled tests.

® = Registered trademark of the BASF-Group in many countries.



We create chemistry

MasterRoc[®] EPB 11

BASF_CC-UAE/Roc_EPB11/v2/03_16

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this BASF publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by BASF either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not BASF, are responsible for carrying out procedures appropriate to a specific application.

BASF Construction Chemicals UAE LLC
P.O. Box 37127, Dubai, UAE
Tel: +971 4 8090800, Fax: +971 4 8851002
www.master-builders-solutions.basf.ae

Disclaimer: the LRQA mark relates to certified management system and not to the product mentioned on this datasheet

