

# MasterSeal<sup>®</sup> GP Foam

## General purpose expanding foam gap filler

### DESCRIPTION

**MasterSeal GP Foam** is a general purpose, single component, expanding construction foam used to create a seal between building elements and around intrusions. It cures through reaction with atmospheric moisture to a semi-flexible foam with tenacious adhesion to most construction materials. When used as a gap filler it ensures stability and flexibility of fixed elements.

### TYPICAL USES

**MasterSeal GP Foam** has been especially developed to provide a simple method for filling irregular gaps and cavities between building elements such as separation walls, ceilings and floors and around intrusions such as pipes, cable trays, conduits and ducting. It is ideal for rapid, economic fixing and sealing around window and door frames.

### ADVANTAGES

- High expansion for maximum yield.
- Bonds perfectly on most substrates without primer: can be universally used.
- Can be used to fill irregular gaps and cavities.
- Simple application.
- Can be shaped and cut after only 1 hour.
- Can be painted or plastered over.
- Low thermal conductivity helps prevent cold gaps and condensation.

### PACKAGING

**MasterSeal GP Foam** is supplied in boxes of 12 x 300ml or 12 x 750ml aerosol cans.

### COLOUR

**MasterSeal GP Foam** is available in Light Yellow.

### WATCHPOINTS

- While the foam does provide a watertight barrier, moisture vapour can pass through.
- Only use in adequately ventilated areas.
- Wear gloves and eye protection. Ensure all floor coverings, curtains, furniture, clothes are protected as the foam has tenacious adhesion to such materials!

### TECHNICAL DATA\*

Cure mechanism	Reaction with atmospheric moisture
Density	20-30kg/m <sup>3</sup>
Cure time (23°C 55% RH)	1-3 hours
Hardening/cutting time (23°C 55% RH)	+/- 60 minutes
Application temperature	+10°C to 35°C
Dimensional stability (FEICA TM 1004)	-5% < DS < 0%
Thermal Conductivity	30 – 35mW/m.K
Acoustic insulation	58dB
Temperature in service	-20°C to +85°C

### APPLICATION

#### Surface preparation:

To ensure optimum adhesion substrates must be sound, clean, dry and free from any loosely adherent material which could prevent adequate bond to the substrate. **MasterSeal GP Foam** adheres perfectly without the use of a primer to most non porous substrates, however adhesion can be promoted by mist spraying the surfaces with clean water.

#### Application:

Ensure that the can temperature is at least 10°C. Remove the cap and screw the spray nozzle onto the connector on top of the canister. Shake the can vigorously before use (at least 30 times). Turn can upside down (proper working position) and press the can's trigger. Fill about 50-60% of the joint, because the foam will expand. If gaps are greater than 40mm deep or wide it is advisable to fill in two stages (to allow atmospheric moisture to achieve full cure). Allow first layer to stiffen for at least 20 minutes before filling remainder of the cavity. Fresh foam can be removed using solvent such as xylene. After curing (60 minutes) the excess foam can be cut and shaped using a knife.

### YIELD / CONSUMPTION RATE

300ml unit will yield approximately 12 litres of foam (0.012m<sup>3</sup>).

750ml unit will yield approximately 45 litres of foam (0.045m<sup>3</sup>).

# MasterSeal® GP Foam

## EQUIPMENT CLEANING

Clean uncured material solvent. Cured material can only be cleaned mechanically. Protect all surrounding areas before use!

## APPLICATION TEMPERATURE RANGE

Minimum +10°C  
Maximum +35°C

## STORAGE AND SHELF LIFE

**MasterSeal GP Foam** has a shelf life of 18 months from production date when stored in its original packaging in a dry place at temperatures between 5°C and 25°C. Store aerosol cans in an upright position.

## HEALTH AND SAFETY

Keep out of reach of children. Extremely flammable. Avoid contact with the skin, eyes and clothing. Only use in well ventilated areas. Wear gloves and eye goggles. Do not smoke, drink or eat during use.

H332: Harmful if inhaled.  
H315: Causes skin irritation.  
H319: Causes serious eye irritation.  
H317: May cause an allergic skin reaction.  
H335: May cause respiratory irritation.  
P211: Do not spray on an open flame or other ignition source.  
P251: Do not pierce or burn, even after use.  
P260: Do not breathe dust/fume/gas/mist/vapours/spray.  
P263: Avoid contact during pregnancy/while nursing.  
P271: Use only outdoors or in a well-ventilated area.  
P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.  
Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

## NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local BASF representative.  
BASF reserves the right to have the true cause of any difficulty determined by accepted test methods.

## QUALITY AND CARE

All products originating from BASF's Dubai, UAE facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001 and OHSAS 18001.

\* Properties listed are based on laboratory controlled tests.

® = Registered trademark of the BASF-Group in many countries.

BASF\_CC-UAE/SI\_GPfoam\_05\_16/v2/11\_16

## STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this BASF publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

## NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by BASF either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not BASF, are responsible for carrying out procedures appropriate to a specific application.