

MasterTile[®] 540

For grouting of wider joints in tiles-up to 12mm wide

DESCRIPTION

MasterTile 540 is a specially designed premixed tile grout tested in accordance with BS 5980: 1984. Requiring only the on site addition of water, **MasterTile 540** is particularly suitable for joints of up to 12mm wide.

PRIMARY USES

Grouting of tile joints up to 12mm wide in both floor and wall tiles.

TYPICAL APPLICATIONS*

Grouting of tile joints up to 12mm wide in the following locations:

- Factories.
- Housing.
- Hospitals.
- Warehouses.
- Swimming pools.
- Power stations.
- Garages.
- And all external tiling.

BENEFITS

- Premixed.
- Non-shrink.
- Specially designed for wide joints up to 12mm wide.
- Good adhesion to dry tiles.
- Easy to use, easily finished.
- Water-resistant.
- Economical.

PACKAGING

MasterTile 540 is available in 25kg packaging.

COLOURS

MasterTile 540 is available in white, sepia, and grey.

APPLICATION PROCEDURE

MIXING INSTRUCTIONS

Mix the powder with water to a thick consistency. No further water should be added.

APPLICATION INSTRUCTIONS

Ensure that the joint to be grouted is clean and that the adhesive is sufficiently set to avoid disturbance of the tiles. Spread the grout over the surface of the tiles with a squeegee, working it fully into the joints. After the initial set has taken place and the grout surface has become fairly firm, spread more grout onto the surface to level the joints. When this has firmed up, use a flat, damp sponge and wipe the surface of the tiles until all the surplus grout is removed.

WATCHPOINTS

During application:

- Avoid exposure to rain, frost, wind or direct heat which may impair the setting of the grout.
- Take normal curing precautions when using cement based products.

COVERAGE

1kg will be sufficient for grouting approximately 27 to 29 metres run of joint 6mm wide x 3mm deep.

MasterTile[®] 540

EQUIPMENT CARE

Clean all equipment immediately after use with water.

SPECIFICATION CLAUSE

MasterTile 540:

All floor and wall tiles shall be grouted using **MasterTile 540** manufactured by BASF, or similar approved manufacturer to the following specification:

Composition Cement based powder containing selected polymers and fillers, suitable for joints up to 12mm.

MASTERTILE 540 shall be used strictly in accordance with the manufacturer's instructions.

HEALTH AND SAFETY

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs. Treat splashes to eyes and skin immediately. If accidentally ingested, seek medical attention. Reseal containers after use. Use in well ventilated areas and avoid inhalation.

STORAGE

Store under cover, clear of the ground on pallets protected from rainfall. Avoid excessive compaction.

Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage advice consult BASF's Technical Services Department.

NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local BASF representative.

BASF reserves the right to have the true cause of any difficulty determined by accepted test methods.

QUALITY AND CARE

All products originating from BASF's Dubai, UAE facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001 and OHSAS 18001.

® = Registered trademark of the BASF-Group in many countries.

BASF_CC-UAE/Tile_540_07_95/v2/05_14

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this BASF publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by BASF either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not BASF, are responsible for carrying out procedures appropriate to a specific application.