

MasterTop[®] F11

High quality, decorative coloured quartz aggregates for use in conjunction with MasterTop Floor Coatings, Ucrete and MasterSeal Traffic Systems

DESCRIPTION

MasterTop F11 coloured, rounded edge quartz aggregates are coated in a thin layer of binder containing the pigments that give the quartz grains their individual colour. They are used with various epoxy and polyurethane products to produce decorative, high strength, durable, trafficable floors with smooth and slip-resistant profiles. Sophisticated colour-coating processes are used to ensure superior bonding of the coating with the quartz body, for effective protection of the floor against all kinds of traffic.

Sizes:

0.3mm – 0.8mm

0.6mm – 1.2mm

PRIMARY USES

MasterTop F11 coloured quartz aggregates are designed to increase the decorative aesthetics, impact and slip resistance of hard wearing, decorative floor coatings and traffic deck systems.

TYPICAL APPLICATIONS

MasterTop F11 coloured quartz aggregates, when used as per the relevant method statements for BASF products can be used in locations such as:

- Carpark decks
- Showrooms and shopping centres
- Food and beverage industry
- General production and packaging areas
- Industrial and commercial kitchens and catering facilities
- Wet processing and production areas
- Shower and changing room areas
- Office and commercial buildings
- Schools and hospitals
- Hotels

Note: In order to obtain best working results it is therefore strongly recommended to carefully and homogeneously blend various batches avoiding high shear forces.

This product is a natural product, which means, that colors may slightly differ from batch to batch respectively from pallet to pallet.

Please use material from only one batch or mix two batches for continuous areas.

ADVANTAGES

- High impact resistance
- Durable
- Highly decorative
- Colour-fast
- Wear resistant
- Non-oxidising
- Slip resistant
- Improves bond
- Reduces dusting

PACKAGING

MasterTop F11 aggregates are available in 25kg bags.

COLOURS

Available in following standard mixes: Smoke, River Rock, Arctic Ice, Cool Red and Silver Stone.

For uni-colours please contact your BASF Representative.

SHELF LIFE

Shelf life is 12 months.

COVERAGE

As per the relevant BASF Product Method Statements.



We create chemistry

MasterTop[®] F11

EQUIPMENT AND CARE

Clean all equipment with water immediately after use.

STORAGE

Store out of direct sunlight, clear of the ground on pallets protected from rainfall. Avoid excessive compaction.

SAFETY PRECAUTIONS

MasterTop F11 aggregates are inert and harmless, however, as with other products containing Portland cement and resins, **MasterTop F11** aggregates mixes may cause irritation. In case of contact with eyes, immediately flush with plenty of water for at least 15 minutes. Call a physician. In case of contact with skin, wash skin thoroughly. For further information refer to the material safety data sheet.

NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local BASF representative.

BASF reserves the right to have the true cause of any difficulty determined by accepted test methods.

QUALITY AND CARE

All products originating from BASF's Dubai, UAE facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001 and OHSAS 18001.

® = Registered trademark of the BASF-Group in many countries.

BASF_CC-UAE/Top_F11_09_16/v1/

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this BASF publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by BASF either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not BASF, are responsible for carrying out procedures appropriate to a specific application.

BASF Construction Chemicals UAE LLC
P.O. Box 37127, Dubai, UAE
Tel: +971 4 8090800, Fax: +971 4 8851002
www.master-builders-solutions.basf.ae

Disclaimer: the LRQA mark relates to certified management system and not to the product mentioned on this datasheet



MASTER[®]
BUILDERS
SOLUTIONS