

# SENERFLEX® Classic Finish

## Description

Factory-mixed, 100% acrylic polymer finish coat. SENERFLEX CLASSIC Finish has a "worm-hole" appearance which is achieved by the random aggregate sizes in the Finish. The "worm-hole" look can be circular, random, vertical or horizontal.



## Primary uses

- Provides an aesthetically pleasing surface colour and texture for the Senergy Wall Systems.
- Can also be utilized as a textured finish for poured concrete or unit masonry, conventional stucco, Senergy Stucco Wall System, Senergy Cement-Board Stucco™, certain insulating concrete forms, and interior veneer plaster or gypsum board (interior application only).

## Packaging

Available in 31.75kg units.

## Colours

Available in a wide variety of standard and custom colours.

## Coverage

(Approximate) 13m<sup>2</sup> per unit

Features	Benefits
100% Acrylic polymer chemistry	Long-term durability and weather resistance
Integral colour	Reduced maintenance and recoating
Weather resistant	Repels water and resists wind-driven rain
Seals existing, non-moving hairline cracks	Protects
Breathable	Doesn't blister, peel or flake

# SENERFLEX<sup>®</sup> Classic Finish

## Mixing

- Thoroughly mix the factory-prepared SENERFLEX CLASSIC Finish with a mixer until thoroughly blended.
- A small amount of clean, potable water may be added to adjust workability.
- Additives are not permitted.
- Close container when not in use.
- Clean tools with soap and water immediately after use.

## Application

- Substrate shall be dry, clean, sound and free of releasing agents, paint or other residue or coatings. Verify substrate is flat, free of fins or planar irregularities greater than 6.4 mm in 3m.
- Apply SENERFLEX CLASSIC Finish directly to the Senergy Base Coat/Reinforcing Mesh with a clean, stainless steel trowel.  
**Note:** In order to minimize the possibility of Base Coat read-through with 330 Maxi-White in CLASSIC, we recommend the use of TINTED PRIMER. Base Coat read-through with SENERFLEX CLASSIC Finish in Maxi-White is very applicator dependent.
- Apply and level SENERFLEX CLASSIC Finish during the same operation to minimum obtainable thickness consistent with uniform coverage.
- Maintain a wet edge on SENERFLEX CLASSIC Finish by applying and texturing continually over the wall surface.
- Work SENERFLEX CLASSIC Finish to corners, joints or other natural breaks and do not allow material to set up within an uninterrupted wall area.
- Float SENERFLEX CLASSIC Finish to achieve final texture.

Note : Minor colour deviations caused by the use of natural stone granular material are possible in different batches. Therefore, only use material from the same batch number for continuous surfaces. Mix the last few pails from one batch with a different batch to minimise any colour differences.

## Limitations

- Protect Senergy materials during transportation and installation to avoid physical damage.
- Store Senergy materials in a cool, dry place protected from freezing. Store at no less than 4°C. Protect from extreme heat and direct sunlight. Shelf life is 9 months when unopened and stored as directed.
- Do not apply Senergy materials in ambient temperatures below 4°C. Provide supplementary heat during installation and drying period (at least 24 hours after installation and until dry) when temperatures less than 4°C prevail.
- Do not apply Senergy materials to frozen surfaces.
- Samples of SENERFLEX CLASSIC Finish are available from Senergy for colour approval only. Samples for job approval must be made in the field by the applicator, and approved prior to ordering.

## Technical Information

Consult the BASF Construction Chemicals Technical Services Department for specific recommendations concerning all other applications. Consult the Senergy website, [www.senergy.cc](http://www.senergy.cc), for additional information about products and systems and for updated literature.

# SENERFLEX<sup>®</sup> Classic Finish

## Health and Safety

### Cautions

May be harmful if vapours or mist are inhaled, if absorbed through skin, or if swallowed. May cause eye, skin and respiratory tract irritation. Swallowing this product can cause kidney damage.

### Precautions

Avoid getting in eyes, on skin, or on clothing. Avoid breathing vapours or mist. Wear safety glasses or goggles, impervious gloves, and clothing with long sleeves and pants. If TLV or PEL can be exceeded, wear respirator selected by a technically qualified person. Wash thoroughly after handling. Wash contaminated clothing before reuse.

### Spills

Wipe up small spills with rags. Absorb larger spills with sand, vermiculite, or kitty litter; sweep up and place in a suitable container for disposal.

### First Aid

- For eye contact, rinse eyes with water. Remove any contact lenses, and continue flushing with plenty of water for several minutes. SEEK MEDICAL ATTENTION if irritation develops and persists.
- For skin contact, wash affected areas with plenty of water, and soap if available, for several minutes. SEEK MEDICAL ATTENTION if irritation develops and persists.
- If inhaled, remove from area to fresh air. SEEK MEDICAL ATTENTION if respiratory irritation develops or if breathing becomes difficult.

- If consumed, give 3-4 glasses of water, but do not induce vomiting unless directed to do so by a physician. Do not give anything by mouth to an unconscious or convulsing person. SEEK MEDICAL ATTENTION.

Read Material Safety Data Sheet before using this product.

#### Note:

BASF Wall Systems is an operating unit of BASF Construction Chemicals, LLC. (herein after referred to as "BASF Wall Systems")

#### Residential Policy

On one and two-family residential framed construction, BASF Wall Systems requires that the wall system selected be one that includes provisions for moisture drainage. The choices include Senturion<sup>®</sup> line of water managed EIFS, commercial SENERFLEX Wall Systems integrating moisture management features, Senergy Stucco Wall System, and Senergy Cement- Board Stucco<sup>™</sup> Systems. Senergy Exterior Surfacing Systems for insulating concrete forms are also acceptable. There are no exceptions to this policy. Under no circumstances will BASF Wall Systems warrant the use of any other system on this type of construction without expressed written authorization from BASF Wall Systems [Residential construction using EIFS on masonry (CMU) or poured concrete does not require the additional water management provisions described above.] See the Senergy Residential Policy Bulletin for a more detailed discussion of this topic. Consult BASF Wall Systems Technical Services Department for specific recommendations concerning all other applications. Consult the Senergy web-site, [www.senergy.cc](http://www.senergy.cc) for additional information about products and systems and for updated literature.

#### Disclaimer

This information and all further technical advice are based on BASF Wall Systems present knowledge and experience. However, BASF assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, BASF Wall Systems disclaims any and all CONDITIONS AND WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. BASF WALL SYSTEMS SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. BASF Wall Systems reserves the right to make any changes according to technological progress or further developments. It is the customers responsibility and obligation to carefully inspect and test any incoming goods. Performance of the product(s) described herein should be verified by testing and carried out only by qualified experts. It is the sole responsibility of the customer to carry out and arrange for any such testing. Reference to trade names used by other companies is neither a recommendation, nor an endorsement of any product and does not imply that similar products could not be used.

BASF\_CC-UAE/Snf\_CLFin\_10\_07/v2/03\_17

### STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this BASF publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

### NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by BASF either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not BASF, are responsible for carrying out procedures appropriate to a specific application.