



We create chemistry

MasterRoc[®] BSG 11

Formerly MEYCO BSG 11

Main Bearing Sealing Grease (Excluder Grease) for Tunnel Boring Machines (TBM)

Product description

MasterRoc BSG 11 is an excluder grease for tunnel boring machines. It effectively protects the main bearing and prevents soil, water or dust ingress into the main bearing sealing. It is formulated to resist high water and ground pressures, and has excellent lubrication and pumping properties as well as excellent adhesion to all surfaces.

Features and benefits

- Excellent sealing and anti-washout properties
- Excellent adhesion to any metal or concrete surfaces
- Excellent pumping and lubricating properties especially at very low or very high temperatures

Packaging

MasterRoc BSG 11 is available in standard 230 kg and 60 kg steel drums for press plate pumps.

Technical data

Form	Homogenous paste, fibrous
Colour	Black
Odour	None
Density [kg/m³] 20°C	1150 ± 50

The information given here is true, represents our best knowledge and is based not only on laboratory work but also on field experience. However, because of numerous factors affecting results, we offer this information without guarantee and no patent liability is assumed. For additional information or questions, please contact your local representative.

Headquarters:

BASF Construction Chemicals Europe Ltd
Global Underground Construction
Im Tiergarten 7, 8055 Zurich Switzerland
Phone +41 58 958 22 11
Fax +41 58 958 32 46

For more information: Visit us: www.ugc.basf.com Contact us: ugc@basf.com

BASF Construction Chemicals offices in Russia, Ukraine, Belarus

OOO "BASF Stroitelnye sistemy"
Moscow: +7 495 225 6436 St. Petersburg: +7 812 332 0412
Kazan: +7 843 212 5506 Krasnodar: +7 861 202 2299
Kiev: BASF T.O.V. +380 44 5915595 Minsk: +375 17 202 2471
E-mail: stroysist@basf.com www.master-builders-solutions.basf.ru

Consistency ISO 2137 [1/10 mm]	250-280
4-ball wear DIN 51350:5 [mm]	< 0.9
Water wash out (38°C) ISO 11009 [%]	< 6
Water spray off (38°C) ASTM D 4049 [%]	< 4
Water resistance DIN 51807/1	0-0
Sealing elastomer compatibility	approved by Merkel, J. Walker
Flash point (base oil)	> 290°C
Biodegradation	inert

Storage

MasterRoc BSG 11 should be stored at 5 - 35°C. If stored in original tightly closed drums it has a shelf life of 12 months.

Safety precautions

MasterRoc BSG 11 is not hazardous and poses no threat to worker safety or the environment. However, it is recommended that all normal precautions be taken when handling the product, such as the use of eye protection and gloves.