



We create chemistry

MasterRoc® BSG 11

Main Bearing Sealing Grease (Excluder Grease) for Tunnel Boring Machines (TBM)

DESCRIPTION OF PRODUCT

MasterRoc® BSG 11 is an excluder grease for tunnel boring machines. It effectively protects the main bearing and prevents soil, water or dust ingress into the main bearing sealing. It is formulated to resist high water and ground pressures, and has excellent lubrication and pumping properties as well as excellent adhesion to all surfaces.

FIELDS OF APPLICATION

- Excellent sealing and anti-washout properties
- Excellent adhesion to any metal or concrete surfaces
- Excellent pumping and lubricating properties especially at very low or very high temperatures

PACKAGING

MasterRoc® BSG 11 is available in standard 230 kg and 60 kg steel drums for press plate pumps.

TECHNICAL DATA

Form	Homogenous Paste, Fibrous
Colour	Black
Odour	None
Density [kg/m ³] 20°C	1150 ± 50
Consistency ISO 2137 [1/10 mm]	250 - 280
4-ball wear DIN 51350:5 [mm]	<0.9
Water wash out (38°C) ISO 11009 [%]	<6
Water spray off (38°C) ASTM D 4049 [%]	<4
Water resistance DIN 51807/1	0 - 0
Sealing Elastomer Compatibility	approved by Merkel, J. Walker
Flash point (base oil)	> 290°C
Biodegradation	inert



We create chemistry

MasterRoc® BSG 11

Main Bearing Sealing Grease (Excluder Grease) for Tunnel Boring Machines (TBM)

STORAGE

MasterRoc® BSG 11 should be stored at 5-35°C. If stored in original tightly closed drums it has a shelf life of 12 months.

SAFETY PRECAUTIONS

MasterRoc® BSG 11 is not hazardous and poses no threat to worker safety or the environment. However, it is recommended that all normal precautions be taken when handling the product, such as the use of eye protection and gloves.

DISCLAIMER

The technical information given in this publication is based on the present state of our best scientific and practical knowledge. **BASF Türk Kimya Sanayi ve Tic. Ltd. Şti.** is only responsible for the quality of the product. **BASF Türk Kimya Sanayi ve Tic. Ltd. Şti.** is not responsible for results that may occur because the product is used other than advised and/or out of instructions regarding the place and the method of use. This technical form is valid only till a new version is implemented and nullifies the old ones.

Contact Information

BASF Türk Kimya San. ve Tic. Ltd. Şti.

Yapı Kimyasalları Bölümü

Tel: 0216 570 34 00

Fax: 0216 570 37 79

Mail: info@master-builders-solutions-turkey.com

www.master-builders-solutions.basf.com.tr

® = Registered trademark of the BASF-Group in many countries of the world

MasterRoc BSG 11 Technical Data Sheet - Issue Date: 02/2016