

# MasterTop<sup>®</sup> THN 2

**Volatile blend of hydrocarbon solvents, specifically designed for cleaning equipment**

## DESCRIPTION

A volatile blend of hydrocarbon solvents, specifically designed for cleaning equipment when using BASF epoxies, polyurethanes and polysulphides.

## TYPICAL PROPERTIES\*

Flashpoint	27°C
Specific gravity	0.860
Colour	clear / yellow liquid

## SHELF LIFE

Indefinite in tightly sealed original containers.

## STORAGE

**MasterTop THN 2** contains a flammable solvent all normal precautions should be taken in both storage and use. Store in closed containers in cool, dry conditions away from sources of ignition.

## SAFETY PRECAUTIONS

Wear goggles, gloves and face mask during use. As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs. Treat splashes to eyes and skin immediately. If accidentally ingested, seek medical attention. Reseal containers after use. Use in well ventilated areas and avoid inhalation.

## NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local BASF representative.

BASF reserves the right to have the true cause of any difficulty determined by accepted test methods.

## QUALITY AND CARE

All products originating from BASF's Dubai, UAE facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001 and OHSAS 18001.

\* Properties listed are based on laboratory controlled tests.

® = Registered trademark of the BASF-Group in many countries.



We create chemistry

# MasterTop<sup>®</sup> THN 2

---

**BASF\_CC-UAE/MTopSolv\_2\_08\_95/v1/12\_13**

**STATEMENT OF RESPONSIBILITY**

The technical information and application advice given in this BASF publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

**NOTE**

Field service where provided does not constitute supervisory responsibility. Suggestions made by BASF either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not BASF, are responsible for carrying out procedures appropriate to a specific application.

**BASF Construction Chemicals UAE LLC**  
P.O. Box 37127, Dubai, UAE  
Tel: +971 4 8090800, Fax: +971 4 8851002  
[www.master-builders-solutions.basf.ae](http://www.master-builders-solutions.basf.ae)

**Disclaimer:** the LRQA mark relates to certified management system and not to the product mentioned on this datasheet



**MASTER<sup>®</sup>  
BUILDERS  
SOLUTIONS**