

MasterRoc[®] BSG 1

Main bearing sealant for Tunnel Boring Machines

Description

MasterRoc BSG 1 is an excluder sealant for tunnel boring machines. It effectively protects the main bearing and prevents water, soil, and dust from entering into the main bearing sealing. It is formulated to resist high water and ground pressures, and has excellent lubrication and pumping properties as well as excellent adhesion to all surfaces.

MasterRoc BSG 1 excluder sealant is highly biodegradable and is based on renewable raw materials.

Applications

Recommended for use in:

- TBM tunneling

Features and Benefits

- Excellent sealing properties
- Excellent anti-washout properties
- Excellent adhesion to any metal or concrete surfaces
- Excellent pumping and lubricating properties
- 'Bio-sealant' entirely based on renewable or natural raw materials

Performance Characteristics

Technical Data

Typical Values

Form	Homogenous paste, fibrous
Color	Black
Odor	None
Density	75 ± 3 lb/ft ³ at 68 °F (1200 ± 50 kg/m ³ at 20 °C)
Consistency ISO 2137 [1/10 mm]	250 to 280
4-ball wear DIN 51350:5 [mm]	< 0.9
Water wash out [98 °F (37 °C)] ISO 11009 [%]	< 5
Water spray off [77 °F (25 °C)] modified ASTM D 4049 [%]	< 7
Water resistance DIN 51807/1	0
Flash point (base oil)	> 545 °F (> 285 °C)
Biodegradation (base oil) CEC-L-33-A-93	> 90%

Sealing elastomer compatibility: Approved by Merkel & J. Walker

Storage and Handling

Storage Temperature: MasterRoc BSG 1 excluder sealant should be stored in unopened, original containers, preferably between 40 °F and 95 °F (5 °C and 35 °C). Shelf life is expected to be 12 months minimum.

Safety: MasterRoc BSG 1 excluder sealant is not hazardous. It is ecologically and environmentally preferable and poses no threat to worker safety or the environment. However, it is recommended that all normal precautions be taken when handling the product, such as the use of eye protection and gloves.

Packaging

MasterRoc BSG 1 excluder sealant is packaged in standard 132 lb (60 kg) and 507 lb (230 kg) steel drums. Other drum sizes and pack weights are available on request.

Related Documents

Safety Data Sheets: MasterRoc BSG 1 excluder sealant

Additional Information

For additional information on MasterRoc BSG 1 excluder sealant, contact your local sales representative.

The Admixture Systems business of BASF's Construction Chemicals division is the leading provider of solutions that improve placement, pumping, finishing, appearance and performance characteristics of specialty concrete used in the ready-mixed, precast, manufactured concrete products, underground construction and paving markets. For over 100 years we have offered reliable products and innovative technologies, and through the Master Builders Solutions brand, we are connected globally with experts from many fields to provide sustainable solutions for the construction industry.

Limited Warranty Notice

BASF warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. **BASF MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS.** The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of BASF. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. **BASF WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.**

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on BASF's present knowledge and experience. However, BASF assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. BASF reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.