

MasterSeal® 940DR / 941DR

Respirable Crystalline Silica-Free Aggregate

PACKAGING

50-lb bags

APPLICABLE SYSTEMS

MasterSeal 940DR:

- MasterSeal 350
- MasterSeal 2530
- MasterSeal 2530 Primerless

MasterSeal 941DR:

- MasterSeal 1500
- MasterSeal 2000
- MasterSeal 2500
- MasterSeal 2500 Primerless
- MasterSeal 2575
- MasterSeal 2575 Primerless

YIELD

See preferred MasterSeal Deck Coating Solution for total system yield.

SHELF LIFE

2 years

STORAGE

Store in unopened containers in a cool, clean, dry area

VOC CONTENT

Not Applicable

DESCRIPTION

MasterSeal 940DR and MasterSeal 941DR aggregates are free of respirable crystalline silica for use in the deck coating systems

PRODUCT HIGHLIGHTS

- MasterSeal 940DR and MasterSeal 941DR aggregates are free of respirable crystalline silica while maintaining all advantages of standard aggregate
- Low dust material
- Made from recycled material
- Broadcast and trowel applications feasible

HOW TO APPLY

SURFACE PREPARATION | MIXING AND APPLICATION

Please see preferred MasterSeal Deck Coating Solution for total system and aggregate surface preparation and application.

TECHNICAL DATA

Composition

MasterSeal 940DR and MasterSeal 941DR are hard-wearing, semi-angular dark grey-green aggregates.

The MasterSeal 940DR is a larger aggregate than the MasterSeal 941DR.

Physical Properties

PROPERTY	RESULTS	TEST METHOD	SYSTEM
Slip Resistance			
940DR	0.775 (wet)	B101.3 with GS-1	MMA Flooring
941DR	0.659 (wet)	B101.3 with GS-1	MasterSeal 1500
Hardness			
940DR	7 MOHS		
941DR	7 MOHS		

Typical Screen Analysis

US SIEVE SIZE	940DR	941DR
12	5–20	2–10
16	28–45	10–30
20	18–30	20–35
30	13–25	20–40
40	2–8	7–22
50	0–3	0–5
70	0–1	0–1
PAN	0–0.5	0–1

HEALTH, SAFETY AND ENVIRONMENTAL

Read, understand and follow all Material Safety Data Sheets and product label information for this product prior to use. The MSDS can be obtained by visiting buildingsystems.basf.com, e-mailing your request to basfbscst@basf.com or calling 1(800)433-9517. Use only as directed.

For medical emergencies only, call ChemTrec® 1(800)424-9300.

LIMITED WARRANTY NOTICE

BASF warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. BASF MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A

PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is the replacement of product or refund of the purchase price, at the sole option of BASF. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. BASF WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on BASF's present knowledge and

experience. However, BASF assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. BASF reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.

