

MasterSeal® Traffic 1500 / 2500 Deck Coating Systems

FORMERLY SONOGUARD® AND CONIPUR® DECK COATING SYSTEMS

BASF Construction Systems recognizes the advantages to having the flexibility to meet the needs of specific projects in the marketplace with innovative solutions. Therefore, the following products have been tested for cross compatibility within the MasterSeal Traffic 1500 and MasterSeal Traffic 2500 lines.

Primers

MasterSeal P 220, MasterSeal P 222,
MasterSeal P 255

Basecoats

MasterSeal M 200, MasterSeal M 265

Topcoats

MasterSeal TC 225, MasterSeal TC 225
Tint-Base, MasterSeal TC 275 Topcoat MasterSeal
TC 295 Topcoat

Systems comprised of any combination of one of the above indicated primers (if required), one basecoat, and one or two topcoats will be recognized as a complete system. Field tests indicate that these products exhibit inter-coat adhesion equal to or better than what is achieved with the standard systems.

Each individual product should be applied as per the published technical data guide recommendations.

For Best Performance

- All systems require mechanical surface preparation, utilizing abrasive shot blasting.
- MasterSeal TC 225 or MasterSeal TC 295 in Gray must be used in applications where color stability and resistance to UV is required.
- Coverage rates must be verified for the anticipated traffic.
- All systems using MasterSeal Traffic 2500 Basecoat must utilize a primer.

All applications utilizing a combination of MasterSeal Traffic 2500 and MasterSeal must be approved, in writing, by BASF Construction Systems to verify the selected product combination is appropriate for anticipated traffic patterns and durability requirements for each individual project.

HEALTH , SAFETY AND ENVIRONMENTAL

Read, understand and follow all Safety Data Sheets and product label information for this product prior to use. The SDS can be obtained by visiting www.master-builders-solutions.basf.us, e-mailing your request to basfbscst@basf.com or calling 1(800) 433-9517. Use only as directed. For medical emergencies only, call ChemTrec® 1(800)424-9300.

LIMITED WARRANTY NOTICE

BASF warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. **BASF MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS.** The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is the replacement of product or refund of the purchase price, at the sole option of BASF. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. **BASF WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.**

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on BASF's present knowledge and experience. However, BASF assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. BASF reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.