

## DECLARATION OF PERFORMANCE

n° IT0019/01

### MasterEmaco N 405 FC

1) Unique identification code of the product type

**EN 1504-2 Methods 2.2/8.2 EN 1504-3 Methods 3.1/3.2/3.3/4.4/7.1/7.2**

2) Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to article 11(4):

**lot number: see packaging of the product**

3) Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**Polymer-modified finishing and levelling mortar (1 – 3 mm) and non-structural repair of concrete structures**

4) Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to article 11(5)

**BASF Construction Chemicals Italia SpA, via Vicinale delle Corti 21, 31100 Treviso**

5) Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2)

not applicable

6) System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 2+**

7) In case of declaration of performance concerning a construction product covered by a harmonized standard:

The notified body ICMQ SpA, identification number 1305, performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued: Certificate of conformity of the factory production control n° 1305-CPR-0805

8) In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not applicable

9) Declared performance

Essential characteristics	Performance	Harmonized technical specification
Compressive strength	Class R2	EN 1504-3: 2005
Chloride content	≤ 0,05 %	
Linear shrinkage	NPD	
Coefficient of thermal expansion	NPD	
Skid resistance	NPD	
Carbonation resistance	NPD	
Elastic modulus	NPD	
Capillary absorption	≤ 0,5 kg/m <sup>2</sup> .h <sup>0,5</sup> ≤ 0,1 kg/m <sup>2</sup> .h <sup>0,5</sup>	EN 1504-3: 2005 EN 1504-2: 2005
Thermal compatibility	≥ 0,8 MPa ≥ 1,0 MPa without traffic ≥ 2,0 MPa with traffic	EN 1504-3: 2005 EN 1504-2: 2005 EN 1504-2: 2005
Adhesion strength	≥ 0,8 MPa ≥ 1,0 MPa without traffic ≥ 2,0 MPa with traffic	EN 1504-3: 2005 EN 1504-2: 2005 EN 1504-2: 2005
Cross cut	NPD	EN 1504-2: 2005
Water vapour permeability	Class I	
Crack bridging ability	NPD	
Artificial weathering	NPD	
Antistatic behavior	NPD	
Adhesion on wet concrete	NPD	
Reaction to fire	Class E	EN 1504-3: 2005 EN 1504-2: 2005
Dangerous substances	Comply with 5.4	

10) The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performances is issued under the sole responsibility of the manufacturer identified in point 4 .

Signed for and on behalf of the manufacturer by:

*Michelotto Dario*

Dario Micheletto

Resp. Quality Control

Treviso, 12 February 2014



We create chemistry