

Unique identification code of the product-type:

MasterFlow 932 AN (DE-T-932/01)

Intended use/es:

**Bonded injection type anchor for use in non-cracked concrete
Post-installed rebar connections**

Manufacturer:

BASF Construction Solutions GmbH, Dr.-Albert-Frank-Strasse 32, 83308 Trostberg

System/s of AVCP:

System 1

European Assessment Document:

ETAG 001 Part 1 and Part 5 : 2013

European Technical Assessment / Technical Assessment Body:

**ETA 15/0561 : 2017 and ETA 15/0562 : 2016
TZUS - Technical and Test Institute for Construction Prague**

Notified body/ies:

TZUS - Technical and Test Institute for Construction Prague (NB 1020)

Declared performance/s:

Essential characteristic	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Characteristic resistance for tension loads - threaded rod	See Annex C 1	System 1	ETA 15/0561
Characteristic resistance for tension loads - rebar	See Annex C 2		
Characteristic resistance for shear loads - threaded rod	See Annex C 3		
Characteristic resistance for shear loads - rebar	See Annex C 4		
Characteristic resistance for tension loads - threaded rod	See Annex C 5		
Characteristic resistance for tension loads - rebar	See Annex C 6		
Characteristic resistance for shear loads - threaded rod	See Annex C 7		
Characteristic resistance for shear loads - rebar	See Annex C 8		
Displacement for threaded rod	See Annex C 9		
Displacement for rebar	See Annex C 10		
Reduction factors for seismic design	See Annex C 11		
Design values of the ultimate bond resistance	See Annex C 1	System 1	ETA 15/0562

The performance of the product identified above is in conformity with the set of declared performance/s.

This declaration of performance is issued, in accordance with Regulations (EU) No 305/2011 and No 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

- Roland Nowicki -