

## DECLARATION OF PERFORMANCE

(n° IT0073/01)

### MasterSeal 528

1) Unique identification code of the product type

**EN 14891**

2) Intended use or uses

**Liquid-applied water impermeable products for use beneath ceramic tiling bonded with adhesives (CM01P)**

3) Manufacturer

**BASF Construction Chemicals Italia SpA, via Vicinale delle Corti 21, 31100 Treviso**

4) System or systems of assessment and verification of constancy of performance (AVCP)

**System 3**

5) Harmonized standard

**EN 14891: 2012**

6) Notified body/ies

**The notified testing laboratory ELLETIPI srl n°1308, carried out the determination of the product-type on the basis of type testing on samples taken by the manufacturer, under system 3, and issued the test report n° 29929/15 rev0 of 05/07/2015**

7) Declared performances

Essential characteristics	Performance	Harmonized technical specification
Waterproofing	No penetration	EN 14891: 2012
Crack bridging ability under standard conditions	≥ 0,75 mm	
Crack bridging ability at low temperature (- 5 °C)	≥ 0,75 mm	
Initial tensile adhesion strenght	≥ 0,5 MPa	
tensile adhesion strenght after water contact	≥ 0,5 MPa	
tensile adhesion strenght after heat ageing	≥ 0,5 MPa	
tensile adhesion strenght after freeze-thaw cycles	≥ 0,5 MPa	
tensile adhesion strenght after contact with chlorinated water	≥ 0,5 MPa	
tensile adhesion strenght after contact with lime water	≥ 0,5 MPa	
Dangerous substances	see SDS	

The performance of the product identified above is in conformity with the set of declared performances .This declaration of performance is issued in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dario Micheletto

Resp. Quality Control

Treviso, 29 September 2015

