

DECLARATION OF PERFORMANCE

No. BE0103/01

1. Unique identification code of the product-type:
MasterSeal 560 JF (No. BE0103/01)
2. Intended use or uses:
EN 998-1 LW CS I
Lightweight rendering mortar (LW)
3. Manufacturer:
BASF Belgium Coordination Center Comm.V.
Business Belux – Construction Chemicals
Nijverheidsweg 89 – Industrieterrein Ravenshout/nr.3711
B – 3945 Ham
4. System/s of AVCP:
System 4
5. Harmonized standard / notified body/ies:
EN 998-1:2010
6. Declared performance(s) (MasterSeal 560 JF)

Essential Characteristics	Performance
Reaction to fire (Euroclass F) EN 13501-1	NPD
Bulk density EN 1015-10 [kg/m ³]	≤ 1300 kg/m ³
Compressive strength EN 1015-11	CS I
Adhesion strength EN 1015-12	0.9 N/mm ² (fracture pattern B)
Capillary water absorption EN 1015-18	WO
Thermal conductivity [W/(m*K)] (Table value according to EN 1745:2012)	$\lambda_{10,dry} \leq 0,27$ W/(m*K) for P=50% $\lambda_{10,dry} \leq 0,30$ W/(m*K) for P=90%
Durability	NPD
Dangerous substances	NPD

NPD: no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. The declaration of performance is issued, in accordance with Regulations (EU) No. 305/2011 and No. 574/2014 under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Christophe de Monie
Site Manager Ham & Supply chain manager EBE for Benelux



Richard Webers
Technical Manager

Ham, 08.09.2016