



We create chemistry

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011
amended by Commissions delegated Regulation (EU) No 574/2014

No 481103

Unique identification code of the product-type: **MasterSeal M 811**

Intended use/es:

EN 1504-2
Surface protection products – Coating

Manufacturer:

BASF Coatings GmbH
Donnerschweer Str. 372
D-26123 Oldenburg

System/s of AVCP:

EN 1504-2: System 2+ (for uses in buildings and civil engineering works)
System 3 (for uses subject to *reaction* to fire regulations)

Harmonised standard:

EN 1504-2:2004

Notified body/ies:

Elletipi s.r.l.
I-44122 Ferrara
(CE identification number: 1308)

Reaction to fire:

Istituto Giordano
I-47814 Bellaria
(CE identification number: 0407)

BASF Coatings GmbH
Donnerschweer Str. 372
D-26123 Oldenburg
Tel.: +49 441 3402 251
www.master-builders-solutions.basf.de

MASTER®
» BUILDERS
SOLUTIONS

Declared performance/s: **EN 1504-2:**

The product **MasterSeal M 811** is used in surface protection system:

MasterSeal Roof 2111

consisting of components:

MasterTop P 604

MasterSeal M 811

MasterSeal TC 269

Table 1: Performance in system

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised Technical specification
Linear shrinkage	NPD	System 2+	EN 1504-2:2004
Compressive strength	NPD		
Coefficient of thermal expansion	NPD		
Abrasion resistance	NPD		
Cross cut	NPD		
Permeability to CO ₂	s _D > 50 m		
Water vapour permeability	class I		
Capillary absorption and permeability to water	w < 0,01 kg/m ² x h ^{0,5}		
Thermal compatibility	> 3 MPa		
Resistance to thermal shock	NPD		
Chemical resistance	NPD		
Resistance to severe chemical attack	reduction in hardness < 50 %		
Crack bridging ability	Static: A5 (23 °C) Dynamic: B4.2 (23 °C)		
Impact resistance	Class III		
Adhesion strength by pull off test	≥ 1,5 N/mm ²		
Reaction to fire	Cfl-s1 Broof-T2	System 3	
Skid resistance	NPD	System 2+	
Artificial aging	OK		
Antistatic behaviour	NPD		
Adhesion on wet concrete	NPD		
Release of dangerous substances	NPD		



We create chemistry

Appropriate Technical Documentation and/or Specific Technical Documentation:

Appropriate Technical Documentation to reaction to fire class Cfl-s1

TR 324099 accor. EN ISO 11925-2
TR 324098 accor. EN ISO 9239-1
CR 324100 accor. EN ISO 13501-1 Cfl-s1

Appropriate Technical Documentation to reaction to fire class Broof-T2

TR 327293 accor. TS 1187:2012
CR 327294 accor. EN ISO 13501-5 Broof-T2

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Oldenburg, 15.09.2015

.....
Klaus Claassen
Product Manager Waterproofing Resins Europe