

MasterRoc[®] SLP 2

Liquid Polymer for soil conditioning in Tunnel Boring Machines

Formerly MEYCO SLF P2*

Description

MasterRoc SLP 2 liquid polymer is used to enhance the performance of the MasterRoc foaming products in difficult ground conditions. MasterRoc SLP 2 liquid polymer is used in coarse soil with low fine content or saturated soil with high water pressure.

MasterRoc SLP 2 liquid polymer can also be used to modify the properties of bentonite slurries for slurry TBM applications.

Applications

Recommended for use in:

- Soil conditioning in Earth Pressure Balance (EPB) shield machines
- Poorly graded and low fine ground, saturated ground and high water pressure ground in EPB shield machines
- Improving the yield and filter cake properties of bentonite slurries; Suitable for bentonite slurries in saline conditions

Features

- Ready-to-use liquid polymer
- Environmentally preferable

Benefits

MasterRoc SLP 2 liquid polymer was designed for soil conditioning with shielded TBM excavation. MasterRoc SLP 2 liquid polymer has excellent performance in restructuring soil and is effective in coarse, clean sands and gravels. When mixed with one of the MasterRoc foams, MasterRoc SLP 2 liquid polymer provides:

- Reduced permeability and increased sealing at the face
- Even and controlled support pressure and increased face stability
- Lower inner friction and lower abrasiveness of the soil at the cutterhead through to the screw conveyor, reducing power consumption and wear to the tools
- Increased cohesion of coarse, clean sands and gravels – smoother soil extraction
- Water soaking and swelling effect, turning wet soil into a more manageable consistency
- Improving the yield of bentonite slurries. Suitable for bentonite slurries in saline conditions

Performance Characteristics

Consumption: Typically, the consumption of MasterRoc SLP 2 liquid polymer is between 0.3 to 4% of the foam solution. In some circumstances, other dosage levels may be required. Contact your local sales representative for assistance.

Technical Data

Form	Viscous Liquid
Color	Light Brown
pH at 68 °F (20 °C)	8.5 to 10.5
Density at 68 °F (20 °C)	56.2 to 59.3 lb/ft ³ (900 to 950 kg/m ³)
Viscosity at 68 °F (20 °C)	<500 cP (mPa.s)

Guidelines for Use

Application: MasterRoc SLP 2 liquid polymer is normally added through a separate pump into the foam solution stream before the foam generator. The mixture is then generated into the foam by the foam generator and injected into the cutterhead and working chamber. MasterRoc SLP 2 liquid polymer can also be added after the foam has been generated and prior to injection to the cutterhead and working chamber. MasterRoc SLP 2 liquid polymer can also be used alone, in which case, it is injected directly to the working chamber or the bottom of the screw conveyor. The quantity of MasterRoc SLP 2 liquid polymer used will vary according to the soil condition.

Consumption: Typically the consumption of MasterRoc SLP 2 liquid polymer is between 0.3 to 4% on the foam solution (0.012 to 0.125 lb/ft³ (0.2 to 2 kg/m³) on the volume of soil excavated). Other dosage levels may be appropriate in certain circumstances, which requires consultation with your local representative.

Storage and Handling

Storage Temperature: MasterRoc SLP 2 liquid polymer should be stored at temperatures between 41 °F and 95 °F (5 °C and 35 °C). Do not allow MasterRoc SLP 2 liquid polymer to freeze. If MasterRoc SLP 2 liquid polymer freezes, contact your local sales representative prior to use.

Shelf Life: MasterRoc SLP 2 liquid polymer has a minimum shelf life of 6 months if stored in original tightly secured containers. Depending on storage conditions, the shelf life may be greater than stated. Please contact your local sales representative regarding suitability for use and dosage recommendations if the shelf life of MasterRoc SLP 2 liquid polymer has been exceeded.

Safety: MasterRoc SLP 2 liquid polymer contains no hazardous materials. However, it is recommended that all normal precautions be taken when handling the product such as the use of eye protection and gloves. Refer to the Safety Data Sheet for MasterRoc SLP 2 liquid polymer for more information.

Packaging

MasterRoc SLP 2 liquid polymer is available in 53 gal (200 L) drums and 264 gal (1,000 L) totes.

Related Documents

Safety Data Sheets: MasterRoc SLP 2 liquid polymer

Additional Information

For additional information on MasterRoc SLP 2 liquid polymer, contact your local sales representative.

The Admixture Systems business of BASF's Construction Chemicals division is the leading provider of solutions that improve placement, pumping, finishing, appearance and performance characteristics of specialty concrete used in the ready-mixed, precast, manufactured concrete products, underground construction and paving markets. For over 100 years we have offered reliable products and innovative technologies, and through the Master Builders Solutions brand, we are connected globally with experts from many fields to provide sustainable solutions for the construction industry.

Limited Warranty Notice

BASF warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. BASF MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of BASF. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. BASF WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on BASF's present knowledge and experience. However, BASF assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. BASF reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.

* MasterRoc P2 became MasterRoc SLP 2 under the Master Builders Solutions brand, effective October, 2013.

© BASF Corporation 2013 ■ 10/13 ■ UGC-DAT-0096

BASF Corporation
Admixture Systems
www.masterbuilders.com

United States
23700 Chagrin Boulevard
Cleveland, Ohio 44122-5544
Tel: 800 628-9990 ■ Fax: 216 839-8821

Canada
1800 Clark Boulevard
Brampton, Ontario L6T 4M7
Tel: 800 387-5862 ■ Fax: 905 792-0651