

More Information

The Master Builders Solutions brand brings all of BASF's expertise together to create chemical solutions for new construction, maintenance, repair and renovation of structures. Master Builders Solutions is built on the experience gained from more than a century in the construction industry.

The know-how and experience of a global community of BASF construction experts form the core of Master Builders Solutions. We combine the right elements from our portfolio to solve your specific construction challenges. We collaborate across areas of expertise and regions and draw on the experience gained from countless construction projects worldwide. We leverage global BASF technologies, as well as our in-depth knowledge of local building needs, to develop innovations that help make you more successful and drive sustainable construction.

The comprehensive portfolio under the Master Builders Solutions brand encompasses concrete admixtures, cement additives, chemical solutions for underground construction, waterproofing solutions, sealants, concrete repair & protection solutions, performance grouts, performance flooring solutions.

Concrete Technology in Focus

Pervious Concrete

Introduction

Also known as porous, no-fines or permeable concrete, pervious concrete is one of the fastest growing applications in the ready-mixed concrete industry. Pervious concrete has the unique ability to allow water to flow through easily, which results in concrete pavements that have no runoff from stormwater or snowmelt.

This Concrete Technology in Focus has been developed to provide an overview of the unique solution developed by BASF specifically for achieving maximum performance of pervious concrete.



Definition

ACI 522R defines pervious concrete as “a zero-slump, open-graded material consisting of portland cement, coarse aggregate, little or no fine aggregates, admixtures, and water. The combination of these ingredients will produce a hardened material with connected pores ranging in size from 0.08 to 0.32 in. (2 to 8 mm), that allow water to pass through easily.”

“The void content can range from 18 to 35%, with typical compressive strengths of 400 to 4000 psi (2.8 to 28 MPa). The drainage rate of pervious concrete pavement will vary with aggregate size and density of the mixture, but will generally fall into the range of 2 to 18 gal/min/ft² (81 to 730 L/min/m²).”

*Effective January 1, 2014, the names of BASF's Master Builders Solutions brand products have changed:
 PolyHeed became MasterPolyheed
 DELVO Stabilizer became MasterSet DELVO
 Rheomac became MasterMatrix VMA
 Navitas 33 became MasterMatrix 33

© Registered trademark of the BASF-Group in many countries
 © BASF Corporation 2015 ■ 01/15 ■ RMX-CTF-0149 ■ LIT #: 3000119

Contact

United States
 23700 Chagrin Boulevard
 Cleveland, Ohio 44122-5544
 Tel: 800 628-9990 ■ Fax: 216 839-8821

Canada
 1800 Clark Boulevard
 Brampton, Ontario L6T 4M7
 Tel: 800 387-5862 ■ Fax: 905 792-0651

www.master-builders-solutions.basf.us

LIMITED WARRANTY NOTICE

We warrant our products to be of good quality and will replace or, at our discretion, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, BASF MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, and BASF shall have no other liability with respect thereto. Any claims regarding product defect must be received in writing within one (1) year from the date of shipment. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of the BASF Technical Manager.

This information and all further technical advice are based on BASF's present knowledge and experience. However, BASF assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. BASF SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. BASF reserves the right to make any changes according to technological progress or further developments.

Applications

Though it may be new in some areas of the country, pervious concrete has been installed since the 1970's in certain parts of the U.S. as an alternative to complex drainage systems and water retention areas.

Typical uses and applications include:

- Parking lots
- Streets, road shoulders
- Bridge embankments
- Edge drains
- Driveways, sidewalks
- Patios, tennis courts
- Swimming pool decks
- Golf cart paths
- Greenhouse floors
- Zoo areas, animal barns

Pervious Concrete Advantage

New federally mandated regulations have made pervious concrete a viable solution for stormwater management. The EPA recognizes pervious concrete as a Best Management Practice (BMP) to help engineers design procedures for treating polluted stormwater. Building owners are realizing better land utilization and LEED credits with pervious concrete parking lots.

Design, Placement and Performance

Pervious concrete must be placed on a well compacted permeable subbase. As water passes through the system, the pervious concrete, subbase, and soil act as a natural filter removing unwanted materials such as oil, grease and other harmful pollutants.

Pervious concrete pavements can be placed using either fixed form set ups or slip-form pavers. With fixed forms, there is typically a riser strip at the top of each form so that the strike off is actually above the final pavement height. Strike off is by vibratory or manual screed and then the riser strips are removed and the pavement is manually compacted with a hand roller. Slip-form paver applications only require one pass.

After jointing pervious concrete, curing is essential. The pervious concrete pavement must be covered with plastic sheeting within 20 minutes from the time the material is discharged from the truck, and allowed to cure for a minimum of 7 days.



Pervious Concrete – Typical Low Slump Mix Challenges

- Difficulty getting the material out of the truck
- Requires addition of water at the job site resulting in inconsistent mix quality
- Accelerated setting time, stiffening
- Short workability window
- Difficult mix to place



BASF System for Pervious Concrete

Through laboratory and field experience, BASF has identified a system of admixtures that helps ready-mixed concrete producers and concrete contractors overcome placement challenges.



How can the BASF System help?

- Allows mix to easily discharge from truck
- No need to add water on site (user-friendly)
- Increases workability time
- Improves flow for ease of placement
- Increases compressive strength
- Inhibits paste drain down



Admixture System Components

- MasterPolyheed® Mid-Range Water-Reducing Admixtures (MRWRs)
- MasterSet® DELVO Hydration-Controlling Admixture (HCA)
- MasterMatrix® Viscosity-Modifying Admixtures (VMAs)
- MasterMatrix® 33 Rheology-Controlling Admixture (RCA)



Admixture System Value Proposition

MasterPolyheed admixtures: These polycarboxylate-based MRWRs provide excellent water reduction and superior cement dispersion and hydration resulting in maximum strength performance. Strength is sometimes a challenge because pervious concrete has a high void content which negatively affects strength. MasterPolyheed admixtures also provide excellent response to vibration of low slump concrete enhancing and facilitating placement.

MasterSet DELVO admixture: Pervious concrete has a low water content and the cement tends to hydrate quickly, resulting in fast concrete setting time and a short workability window. MasterSet DELVO admixture is used to slow down the rate of cement hydration and extend the mix workability window which allows for easier and faster concrete placement. The use of MasterSet DELVO admixture in pervious concrete eliminates the need for job site retempering with water.

MasterMatrix VMA admixtures and MasterMatrix 33 admixture:

Since pervious concrete is a harsh mix, these VMAs add body and MasterMatrix 33 rheology-controlling admixture helps lubricate low slump mixes. The result is better mix flow and faster discharge time from the truck, easier placement and compaction. In addition, the use of MasterMatrix VMA admixtures is an insurance policy to help prevent paste drain down and significantly increase compressive and flexural strength in low compaction pervious concrete mixes.

The combination of these products has significantly improved the mixing and handling of pervious concrete. For more information on suggested dosages for pervious concrete applications, contact your local sales representative.

