

MasterRoc® SWA 710

Strong Thickener for Soil Conditioning in Tunnel Boring Machines (TBM)

DESCRIPTION

MasterRoc® SWA 710 is a liquid polymer, which is specifically designed for its use in ground and slurry conditioning. **MasterRoc® SWA 710** works as a binding agent restructuring the soil with a poor grading and low fines content, increasing its plasticity and cohesion, which helps to improve the balance of pressure in the working chamber, leading to better ground stability and soil extraction. **MasterRoc® SWA 710** can be used to enhance the performance of **MasterRoc SLF** foams and ACP soil conditioning products in difficult ground conditions, for example, in coarse soil with low fine content, or saturated soil with high water pressure. **MasterRoc® SWA 710** is also suitable to use for an adequate sealing of the excavation face during hyperbaric interventions in combination with the injection of bentonite or filler slurries.

FIELDS OF APPLICATION

- EPB and Slurry TBMs
- High ground water pressures, poorly graded or ground containing low amount of fine particles, water saturated ground, and
- Bentonite slurry modification in case of high soil porosity or saline water conditions.
- Improving the yield and filter cake properties of bentonite and filler slurries.
- Lubricant for pipe jacking.

FEATURES AND BENEFITS

- Structuring the soil, particularly effective in, coarse, clean sands and gravels below groundwater.
- Reducing soil permeability.
- Creation of plastic deformation properties in the soil providing an even and controlled support pressure and increased face stability.
- Lowering the inner friction and abrasiveness of the soil. Increasing cohesion of coarse sands and gravels.
- Improves the yield and filter cake properties of bentonite slurries.
- Ready to use - no mixing equipment required.

PACKAGING

MasterRoc® SWA 710 is available in 1000 liter IBC's.

Technical data	
Form	Liquid
Color	White
Density [kg/m ³] 20°C	1.05
pH 20°C	7
Viscosity (DIN EN ISO 3219, 23°C, 250 1/s)	750 mPa.s
Solubility in water	Miscible

APPLICATION PROCEDURE

MasterRoc® SWA 710 should be used independently, in which case it is injected directly to the working chamber or the screw conveyor.

The quantity of **MasterRoc® SWA 710** polymer needed depends on the soil conditions.

For the combination with other soil conditioning agents, please contact your local BASF representative.

CONSUMPTION

Trials should be conducted to determine the optimum concentration of polymer. The dosage depends on the application field and the amount of water content in slurry or excavated ground – please consult your local BASF representative.

STORAGE

The storage temperature of **MasterRoc® SWA 710** is between 5°C and 35°C. If stored in original, tightly closed containers under the above conditions, it will have a shelf life of 6 months. Do not allow the product to freeze. Please contact your local BASF representative prior to the use of any product that has frozen.

MasterRoc[®] SWA 710

SAFETY PRECAUTIONS

MasterRoc[®] SWA 710 contains no hazardous substances. However, standard precautions for handling chemical products should be observed. Avoid eye and skin contact and wear rubber gloves. For further information, refer to the Material Safety Data Sheet.

NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local BASF representative.

BASF reserves the right to have the true cause of any difficulty determined by accepted test methods.

QUALITY AND CARE

All products originating from BASF's Dubai, UAE facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001 and ISO 45001.

* Properties listed are based on laboratory controlled tests.

® = Registered trademark of the BASF-Group in many countries.

BASF_CC-UAE/Roc_SWA710_12_18

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this BASF publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by BASF either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not BASF, are responsible for carrying out procedures appropriate to a specific application.

BASF Construction Chemicals UAE LLC
P.O. Box 37127, Dubai, UAE
Tel: +971 4 8090800 Fax: +971 4 8851002
www.master-builders-solutions.basf.ae

Disclaimer: the LRQA mark relates to certified management system and not to the product mentioned on this datasheet



MASTER[®]
» BUILDERS
SOLUTIONS